

Modicon M171/M172 logic controllers for HVAC solutions

Remote displays for M172 logic controllers



TM172DCLWT●●




TM172DCLFW



TM172DCLFG



TM172DGRP



TM172ABKPG



TM171ABKPG

Remote displays					
Type	Description	Housing	Built-in sensor for	Reference	Weight kg/lb
Remote color touch screen wall mounting displays	- Power supply: 24 V $\sim$ - Color touchscreen - Size: 3.5" - Resolution: 320 x 240 pixels - IP20 - Communication port: 1 RS485, Modbus SL with terminal blocks	White	Temperature	TM172DCLWT	0.340/ 0.749
			- Temperature - Relative humidity	TM172DCLWTH	0.340/ 0.749
			- Temperature - Relative humidity - Presence PIR	TM172DCLWTHP	0.340/ 0.749
Remote color touch screen flush mounting displays	- Power supply: 24 V $\sim$ - Color touchscreen - Size: 3.5" - Resolution: 320 x 240 pixels - IP65 (front face) - Communication port: 1 RS485, Modbus SL with terminal blocks	White	–	TM172DCLFW	0.205/ 0.452
		Grey	–	TM172DCLFG	0.205/ 0.452
Remote display monochrome	5 control keys - Backlit LCD, 240 x 140 pixels, - Monochrome, - With real time clock	Grey		TM172DGRP	0.197/ 0.430
Accessories to be ordered separately					
Type	Use			Reference	Weight kg/lb
Mounting accessories (1)	White wall support for TM172DCLFW display			TM172ABKPW	0.060/ 0.132
	Grey wall support for TM172DCLFG display			TM172ABKPG	0.060/ 0.132
	Wall bracket For TM172DGRP display			TM171ABKPG	0.015/ 0.030

(1) With the use of TM172ABKP●● accessories, the degree of protection for the TM172DCLF● displays is IP20.