

PRODUCT-DETAILS

ACS580-01-088A-4

LV AC general purpose wall-mounted drive, IEC:
Pn 45 kW, 88 A, 400 V, 480 V (ACS580-01-088A-4)



General Information

Global Commercial Alias	ACS580-01-088A-4
Product ID	3AUA0000080502
ABB Type Designation	ACS580-01-088A-4
EAN	6438177305583
Catalog Description	LV AC general purpose wall-mounted drive, IEC: Pn 45 kW, 88 A, 400 V, 480 V (ACS580-01-088A-4)

The ACS580-01 is plug-in ready to control your compressors, conveyors, pumps, extruders, centrifuges, mixers, fans and many other variable and constant torque applications, in a variety of light industries, including food and beverage, plastic, textile, material handling, and agriculture.

Long Description

All essential features are built-in as standard, simplifying drive selection, and making additional hardware unnecessary. Versatile and straightforward settings menu and assistants enable fast setup, commissioning, use and maintenance, while rugged and robust design makes it a good fit for various environments. With the ACS580 drives you can easily take full control of your processes to comprehensively manage your plant. The wall-mounted ACS580-01 comes in IP21 enclosure as standard. Also, IP55 and flange mounting units are available.

Ordering

Country of Origin	Finland (FI)
Customs Tariff Number	85044086
HS Code	850440-- Electrical transformers, static converters (for example, rectifiers) and inductors.- Static converters
Invoice Description	ACS580-01-088A-4 PN: 45 kW, IN: 88 A

Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

Container Information

Gross Volume	43.836 dm ³
--------------	------------------------

Dimensions

Product Net Weight	28.3 kg 62.391 lb
Product Net Depth / Length	295.00 mm 11.61 in
Product Net Height	732.00 mm 28.82 in
Product Net Width	203.00 mm 7.99 in
Package Level 1 Depth / Length	835.00 mm 32.874 in
Package Level 1 Height	521.00 mm 20.512 in
Package Level 1 Width	295.00 mm 11.614 in
Package Level 1 Units	1 carton

Technical

Number of Phases	3
Degree of Protection	IP21
Enclosure Type NEMA	Type1
Altitude	1000 m
Sound dB (A)	95
Multiple Battery Information	Lithium Coin, CR2032, 220 mAh, 3 V, 1 pc, 3 g
Frequency (f)	47.5 ... 63 Hz
Frame Size	R5
Input Voltage (U _{in})	380 ... 480 V
Mounting Type	Wall-mounted
Communication Protocol	CAN DeviceNet EtherNet/IP MODBUS Other Bus Systems PROFIBUS PROFINET IO TCP/IP
Number of Hardware Interfaces	Industrial Ethernet 0 Other 2 Parallel 2 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1
Includes	Control unit PC connection
Analog Inputs	2

Analog Outputs	2
Number of Digital In/Outputs	6 / 3
Output Current, Heavy-Duty Use (I_{HD})	72 A
Output Current, Light-Overload Use (I_{LD})	83 A
Output Current, Normal Use (I_n)	88 A
Output Power, Heavy-Duty Use (P_{HD})	37 kW
Output Power, Light-Overload Use (P_{LD})	45 kW
Output Power, Normal Use (P_n)	45 kW
Apparent Power Output	61 kV·A
Efficiency Level	IE2
Standby Loss	21 W
Complete Drive Module Efficiency (61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	294 W	91.9 %	0.5 %
0/50 %	402 W	94.1 %	0.7 %
0/100 %	767 W	94.3 %	1.3 %
50/25 %	325 W	95.5 %	0.5 %
50/50 %	469 W	96.6 %	0.8 %
50/100 %	915 W	96.6 %	1.5 %
90/50 %	545 W	97.8 %	0.9 %
90/100 %	1139 W	97.6 %	1.9 %

Temperature Rating	Maximum 40 °C Minimum -15 °C
--------------------	---------------------------------

Classifications

ETIM 8	EC001857 - Frequency converter =< 1 kV
ETIM 9	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

Environmental

SCIP	24d7f559-8ddc-4469-93c7-ad912823d754 Finland (FI)
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Additional Information

Product Main Type	ACS580-01
Product Name	Frequency converter

Categories

Drives → Low Voltage AC Drives → General Purpose Drives → ACS580-01 - Wall-mounted drive

