

S1-M2-25



Products Low Voltage Products and Systems Control Products Manual Motor Starters Manual Motor Starters Accessories

General Information

Extended Product Type:	S1-M2-25
Product ID:	1SAM201907R1102
EAN:	4013614400810
Catalog Description:	S1-M2-25 Power Infeed Block
Long Description:	S1-M2-25 3-phase power infeed block High, for MS116 / MS132, 25mm2

Additional Information

Ambient Air Temperature:	Operation -25 +70 °C Storage -50 ...+80 °C
Ampere Rating UL/CSA:	65 A
Connecting Capacity Main Circuit UL/CSA:	Stranded 1/2x 10 ... 4 AWG Flexible 1/2x 10 ... 6 AWG
Connecting Capacity Main Circuit:	Rigid 1x 6 ... 25 mm ² Flexible 1x 6 ... 16 mm ²
Country of Origin:	Germany (DE)
Customs Tariff Number:	85369010
Data Sheet, Technical Information:	1SBC100192C02--
Declaration of Conformity - CE:	1SAD938510-0056
Degree of Protection:	IP20
Dimension Diagram:	1SAM200451F0002
E-number:	3111688
EAN:	4013614400810
EPLAN Catalog Tree:	Electrical engineering / Protection devices / Motor overload switch
ETIM 4:	EC002498 - Accessories for low-voltage switch technology
ETIM 5:	EC002498 - Accessories for low-voltage switch technology
ETIM 6:	EC002498 - Accessories for low-voltage switch technology
GOST Certificate:	1SAA937000-2703
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	2CDC131011M6802 2CDC131034M6801 2CDC131022M6802
Invoice Description:	S1-M2-25 3-phase power infeed block High, for MS116 / MS132, 25mm2
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
Minimum Order Quantity:	1 piece
Object Classification Code:	X
Package Level 1 EAN:	4013614488191
Package Level 1 Gross Weight:	0.548 kg
Package Level 1 Height:	46 mm
Package Level 1 Length:	181 mm
Package Level 1 Units:	10 piece
Package Level 1 Width:	80 mm
Product Main Type:	S1
Product Name:	Power Infeed Block
Product Net Depth:	27 mm
Product Net Height:	53.8 mm

Product Net Weight:	0.051 kg
Product Net Width:	48 mm
Rated Operational Current (I _b):	65 A
Rated Operational Voltage:	690 V
Recommended Screw Driver:	Pozidriv 2 M3.5
RoHS Date:	0159
RoHS Information:	1SAA963003-4402
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Selling Unit of Measure:	piece
Short Description:	S1-M2-25 3-phase power infeed block
Standards:	IEC/EN 60947-1 IEC/EN 60947-4-1 UL 60947-1 UL 60947-4-1
Suitable For:	MS116 MS132
Suitable for Product Class:	Manual Motor Starter
Tightening Torque:	Main Circuit 2.5 N·m
Tightening Torque UL/CSA:	Main Circuit 22 in·lb
UL Certificate:	1SAA963001-1602
UNSPSC:	39120000
Wire Stripping Length:	Main Circuit 10 mm
cUL Certificate:	1SAA963001-1701
eClass:	7.0 27379201

