



\*\*\*spare part\*\*\* SIPLUS S7-300 SM 331 AI 8x0/4...20 mA based on 6ES7331-7TF01-0AB0 with conformal coating, -25...+70 °C,

Figure similar

General information	
based on	<a href="#">6ES7331-7TF01-0AB0</a>
Product function	
<ul style="list-style-type: none"> <li>• Isochronous mode</li> </ul>	No
Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> <li>• Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>• Reverse polarity protection</li> </ul>	Yes
Input current	
from load voltage L+ (without load), max.	20 mA
from backplane bus 5 V DC, max.	120 mA
Output voltage	
Power supply to the transmitters	
<ul style="list-style-type: none"> <li>• Rated value (DC)</li> </ul>	24 V
Power loss	
Power loss, typ.	1.5 W
Analog inputs	
Number of analog inputs	8
permissible input current for current input (destruction limit), max.	40 mA
Input ranges	
<ul style="list-style-type: none"> <li>• Voltage</li> </ul>	No
<ul style="list-style-type: none"> <li>• Current</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Thermocouple</li> </ul>	No
<ul style="list-style-type: none"> <li>• Resistance thermometer</li> </ul>	No
<ul style="list-style-type: none"> <li>• Resistance</li> </ul>	No
Input ranges (rated values), currents	
<ul style="list-style-type: none"> <li>• 0 to 20 mA                             <ul style="list-style-type: none"> <li>— Input resistance (0 to 20 mA)</li> </ul> </li> </ul>	240 Ω
<ul style="list-style-type: none"> <li>• -20 mA to +20 mA                             <ul style="list-style-type: none"> <li>— Input resistance (-20 mA to +20 mA)</li> </ul> </li> </ul>	240 Ω
<ul style="list-style-type: none"> <li>• 4 mA to 20 mA                             <ul style="list-style-type: none"> <li>— Input resistance (4 mA to 20 mA)</li> </ul> </li> </ul>	240 Ω
Cable length	
<ul style="list-style-type: none"> <li>• shielded, max.</li> </ul>	800 m
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> <li>• Resolution with overrange (bit including sign), max.</li> </ul>	16 bit

• Integration time, parameterizable	Yes
• Integration time (ms)	20 ms at 50 Hz; 16.6 ms at 60 Hz; 100 ms at 100 Hz
• Interference voltage suppression for interference frequency f1 in Hz	10 / 50 / 60 Hz

### Encoder

#### Connection of signal encoders

• for current measurement as 2-wire transducer	Yes
• for current measurement as 4-wire transducer	Yes

### Errors/accuracies

#### Operational error limit in overall temperature range

• Current, relative to input range, (+/-)	0.15 %; ±0.25 % @ < 0 °C or > 60 °C
---	-------------------------------------

#### Basic error limit (operational limit at 25 °C)

• Current, relative to input range, (+/-)	0.1 %
---	-------

### Interrupts/diagnostics/status information

Diagnostics function	Yes
----------------------	-----

#### Alarms

• Diagnostic alarm	Yes
• Limit value alarm	Yes

#### Diagnoses

• Diagnostic information readable	Yes
-----------------------------------	-----

#### Diagnostics indication LED

• Group error SF (red)	Yes
------------------------	-----

### Potential separation

#### Potential separation analog inputs

• between the channels	No
• between the channels, in groups of	8
• between the channels and backplane bus	Yes
• between the channels and the power supply of the electronics	Yes

### Isolation

Isolation tested with	500
-----------------------	-----

### Standards, approvals, certificates

CE mark	Yes
---------	-----

UL approval	Yes; File E239877
-------------	-------------------

RCM (formerly C-TICK)	Yes
-----------------------	-----

KC approval	Yes
-------------	-----

EAC (formerly Gost-R)	Yes
-----------------------	-----

#### Railway application

• EN 50121-4	No
• EN 50155	No

### Ambient conditions

#### Ambient temperature during operation

• min.	-25 °C; = Tmin
• max.	70 °C; = Tmax; 60 °C @ UL/cUL use

#### Ambient temperature during storage/transportation

• min.	-40 °C
• max.	70 °C

#### Altitude during operation relating to sea level

• Installation altitude above sea level, max.	5 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)

#### Relative humidity

• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
---	---

#### Resistance

##### Use in stationary industrial systems

— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *

— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
<b>Use on ships/at sea</b>	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
<b>Usage in industrial process technology</b>	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
<b>Remark</b>	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!

**Connection method**

required front connector	20-pin
--------------------------	--------

**Dimensions**

Width	40 mm
Height	125 mm
Depth	117 mm

**Weights**

Weight, approx.	205 g
-----------------	-------

**Classifications**

	Version	Classification
eClass	14	27-24-22-01
eClass	12	27-24-22-01
eClass	9.1	27-24-22-01
eClass	9	27-24-22-01
eClass	8	27-24-22-01
eClass	7.1	27-24-22-01
eClass	6	27-24-22-01
ETIM	10	EC001420
ETIM	9	EC001420
ETIM	8	EC001420
ETIM	7	EC001420
IDEA	4	3562
UNSPSC	15	32-15-17-05

**Approvals / Certificates**

**General Product Approval**



[Manufacturer Declaration](#)



[China RoHS](#)



**EMV For use in hazardous locations**



[CCC-Ex](#)

last modified:

5/29/2024

