

Siemens
EcoTech



Figure similar

RCBO, Icn: 6 kA, 1P+N, type A, 30 mA, C-Char, In: 40 A, Un AC: 240 V, pigtail 600 mm

Model	
product brand name	SENTRON
product designation	RCD-operated circuit breaker
design of the product	Instantaneous
General technical data	
number of poles	2
number of poles with protection	1
design of pole	1P+N
tripping characteristic class	C
overvoltage category	3
degree of pollution	2
Voltage	
type of voltage of the operating voltage	AC
insulation voltage (Ui) rated value	264 V
surge voltage resistance rated value	4 000 V
surge current resistance at (8/20) µs	1 kA
tripping fault current rated value	30 mA
• operational current	
— at 30 °C rated value	40 A
— at 40 °C rated value	38 A
— at 45 °C rated value	36.8 A
— at 50 °C rated value	36 A
— at 55 °C rated value	34.8 A
• operational current at AC rated value	40 A
residual current type	A
Supply voltage	
supply voltage	
• at AC rated value	230/240 V
• for testing equipment minimum	195 V
operating frequency	50/60 Hz
supply voltage frequency rated value	50 Hz
Protection class	
protection class IP	IP20, if the distribution board is installed, with connected conductors
Breaking Capacity	

switching capacity current		
• according to EN 60898 rated value	6 kA	
• according to IEC 60947-2 rated value	6 kA	
short-circuit current breaking capacity (Icn) according to EN 61009-1 rated value	6 kA	
rated residual switching capacity (IΔm) according to IEC 61009-1	4.5 kA	
energy limitation class	3	
Dissipation		
power loss [W]		
• for rated value of the current at AC in hot operating state per pole	5.16 W	
• maximum	9.7 W	
Product details		
product feature touch protection	Yes	
product component neutral conductor switching	Yes	
product feature silicon-free	Yes	
Product function		
product function	voltage dependent RCD function	
Connections		
connectable conductor cross-section using the upper clamping point without core end processing		
• minimum	0.75 mm²	
• maximum	35 mm²	
connectable conductor cross-section solid		
• minimum	0.75 mm²	
• maximum	16 mm²	
connectable conductor cross-section stranded		
• minimum	0.75 mm²	
• maximum	16 mm²	
connectable conductor cross-section finely stranded with core end processing		
• minimum	0.75 mm²	
• maximum	10 mm²	
tightening torque with screw-type terminals		
• minimum	1.2 N·m	
• maximum	2 N·m	
position of power supply cord	from below	
Mechanical Design		
height	90 mm	
width	18 mm	
depth	77 mm	
installation depth	70 mm	
number of modular width units	1	
mounting position	any	
Net Weight	164 g	
weight with packaging	155 g	
Environmental conditions		
influence of the surrounding temperature	Max. 95% humidity	
ambient temperature during operation		
• minimum	-25 °C	
• maximum	55 °C	
ambient temperature during storage		
• minimum	-40 °C	
• maximum	75 °C	
number of test cycles for environmental testing according to IEC 60068-2-30	28	
Approvals Certificates		
General Product Approval	other	Environment



[Confirmation](#)



Environment

[Environmental Con-
firmations](#)

[Environmental Con-
firmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SV9316-7PK40>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SV9316-7PK40>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SV9316-7PK40

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP='HAUPT'></mmp_prod_no>)

last modified:

7/22/2025

