

Article No. : 6SL3310-1GH34-7AA3



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data

Input		
Supply frequency	47...63 Hz	
Supply voltage	690 V ±10 %	
Rated input current	483 A	
Max. current	740 A	
Pulse number	6	
Energy recovery capability	No	(2Q)

Output		
Output voltage	690 V	
Rated power (LO) in kW	450 kW	
Rated power (HO) in kW	400 kW	
Rated output current	465 A	
Rated output current (LO)	452 A	
Rated output current (HO)	416 A	
Output current Max	678 A	
Pulse frequency (factory setting)	1.25 kHz	

Basic data


Power losses ΔP	8.03 kW
Sound pressure level L _{pA} (1 m)	70 dB
Conductor cross section, max. (IEC)	4 x 240 mm ²
Degree of protection	IP00
Dimensions (H x W x D)	1,506 mm x 503 mm x 540 mm
Weight approx.	294 kg
Frame size	HX

Environmental conditions

Installation altitude	1,000 m
Coolant	Air
Coolant requirement, air	0.78 m ³ /s
Ambient temperature	0 °C - +40 °C

Converter losses to IEC61800-9-2*

Efficiency class	IE2
Comparison with the reference converter (90% / 100%)	35.4 %



The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard IEC61800-9-2) of the relative torque generating current (I) over the relative motor stator frequency (f). The values are valid for the basic version of the converter without options/components.

*calculated values

Special design

Line-side power components

Load-side power components

DC link components

Supplementary system components

6SL30401GA011AA0 - Control Unit Kit CU320-2 PN (PROFINET, EtherNet/IP)