


Product datasheet

Specifications



current limiting block - 63 A - for P25M

21115

⚠ Discontinued on: Jun 30, 2023 AD

⚠ To be discontinued

Main

Circuit breaker application	Control circuit
Range of product	P25M
Product or component type	Current limiting module
Device short name	limiter block
Poles description	3P

Complementary

[In] rated current	63 A
Breaking capacity	100 kA at 415 V AC
Mounting mode	Fixed downside Fixed upside
Mounting support	Plug-in
9 mm pitches	5
Connections - terminals	Tunnel type terminals25 mm ² flexible

Environment

Standards	IEC 947-2 IEC 947-4
Product certifications	NEMKO CEBEC SEMKO DEMKO

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.0 cm
Package 1 Width	4.5 cm
Package 1 Length	4.5 cm
Package 1 Weight	117.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	30
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm

Package 2 Length	40.0 cm
------------------	---------

Package 2 Weight	3.86 kg
------------------	---------

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Longer




Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins