

Product datasheet

Specifications



fuse-switch disconnecter D02 - 1 pole +N - 63 A

MGN02663

⚠ Discontinued on: 30 Jun 2023

⚠ Discontinued

Main

Range	Acti9
Product name	Acti9 D0
Product or component type	Fuse-switch disconnecter
Device short name	D02
Poles description	1P + N
Number of protected poles	1
Utilisation category	AC-22A conforming to IEC 60947-3

Complementary

[In] rated current	63 A
fuse curve	GG AM
Fuse size	15 x 36 mm
Fuse size code	D02
[Ue] rated operational voltage	230...400 V AC 50/60 Hz
[Ui] rated insulation voltage	400 V
[Uimp] rated impulse withstand voltage	6 kV
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	6
Height	88 mm
Width	72 mm
Depth	68 mm
Mechanical durability	8500 cycles open-close
Electrical durability	1500 cycles
Connections - terminals	Screw clamp terminals 1.5...35 mm ² rigid Screw clamp terminals 1.5...25 mm ² flexible Screw clamp terminals 1.5...25 mm ² flexible with cable end
Wire stripping length	14 mm
Tightening torque	3 N.m

Environment

Standards	IEC 60269-3 EN 60947-1 IEC 60269-1 EN 60947-3 IEC 60947-1 IEC 60947-3
Quality labels	VDE
IP degree of protection	IP20
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-25...55 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.5 cm
Package 1 Width	5.4 cm
Package 1 Length	9 cm
Package 1 Weight	254 g
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Height	8.5 cm
Package 2 Width	9.8 cm
Package 2 Length	33 cm
Package 2 Weight	1.59 kg
Unit Type of Package 3	S03
Number of Units in Package 3	36
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	10.117 kg

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging without single use plastic

Yes

EU RoHS Directive

[Compliant](#)

Halogen-free status

Halogen free product

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

Take-back

No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins