

Product datasheet

Specifications



TeSys F - contactor coil - LX4FJ - 375V DC

LX4FJ375

⚠ Discontinued

Main

Range	TeSys
Product or component type	Contactor coil
Device short name	LX4FJ
Range compatibility	TeSys TeSys F LC1F contactor
Product compatibility	LC1F400
Control circuit type	DC low consumption
[Uc] control circuit voltage	375 V DC
Inductance of closed circuit	4435 H
Average resistance	236 Ohm inrush at 20 °C 33750 Ohm holding at 20 °C
Operating time	45...60 ms opening 50...60 ms closing
Mechanical durability	10 Mcycles
Maximum operating rate	2400 cyc/h 55 °C

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Drop-out: 0.2...0.35 Uc (at 55 °C) Operational: 0.85...1.1 Uc (at 55 °C)
Inrush power in W	1000 W (at 20 °C)
Hold-in power consumption in W	6 W at 20 °C

Environment

Ambient air temperature for operation	-5...55 °C
Product weight	0.97 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Longer



Lifetime extension

Repair

No