


## Specifications



396735555

A9C15409

**EAN Code: 3606480374906**

|                              |                                                                                                                           |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| range of product             | Acti9                                                                                                                     |
| Device short name            | iATLc+s                                                                                                                   |
| Product or component type    | Centralized control and remote indication auxiliary                                                                       |
| Signal contacts composition  | 1 C/O                                                                                                                     |
| Signalling circuit voltage   | 24 V AC/DC: 10 mA<br>12...240 V AC: 50/60 Hz 6 A<br>12...24 V DC: 6 A<br>15...240 V AC: 50/60 Hz 2 A<br>13...24 V DC: 2 A |
| [Uc] control circuit voltage | 24...240 V AC 50/60 Hz                                                                                                    |

|                                        |                                                                                                                                                                                                                  |
|----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Ui] rated insulation voltage          | 440 V                                                                                                                                                                                                            |
| [Uimp] rated impulse withstand voltage | 4 kV                                                                                                                                                                                                             |
| Mounting mode                          | Fixed, on right side of TL                                                                                                                                                                                       |
| Mounting support                       | DIN rail                                                                                                                                                                                                         |
| 9 mm pitches                           | 2                                                                                                                                                                                                                |
| Height                                 | 86 mm                                                                                                                                                                                                            |
| Width                                  | 18 mm                                                                                                                                                                                                            |
| Depth                                  | 71 mm                                                                                                                                                                                                            |
| Colour                                 | White                                                                                                                                                                                                            |
| Connections - terminals                | Tunnel type terminals0.5...4 mm² - rigid<br>Tunnel type terminals0.5...4 mm² - rigid - with cable end<br>Tunnel type terminals1...4 mm² - flexible<br>Tunnel type terminals1...4 mm² - flexible - with cable end |
| Wire stripping length                  | 11 mm                                                                                                                                                                                                            |
| Tightening torque                      | 1 N.m                                                                                                                                                                                                            |
| Range compatibility                    | Acti9 iTL<br>Acti9 iTLi<br>Acti9 iTLs                                                                                                                                                                            |
| Product compatibility                  | ITL (32 A)<br>ITL (16 A)                                                                                                                                                                                         |

|                         |                              |
|-------------------------|------------------------------|
| Overvoltage category    | III                          |
| IP degree of protection | IP20 conforming to IEC 60529 |
| Tropicalisation         | 2                            |

|                                       |                  |
|---------------------------------------|------------------|
| Relative humidity                     | 95 % at 55 °C    |
| Ambient air temperature for operation | -20...50 °C      |
| Ambient air temperature for storage   | -40...70 °C      |
| Standards                             | EN/IEC 60669-2-2 |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 8.000 cm  |
| Package 1 Width              | 2.900 cm  |
| Package 1 Length             | 9.000 cm  |
| Package 1 Weight             | 75.000 g  |
| Unit Type of Package 2       | BB1       |
| Number of Units in Package 2 | 8         |
| Package 2 Height             | 8.500 cm  |
| Package 2 Width              | 9.200 cm  |
| Package 2 Length             | 26.500 cm |
| Package 2 Weight             | 657.000 g |
| Unit Type of Package 3       | S03       |
| Number of Units in Package 3 | 72        |
| Package 3 Height             | 30.000 cm |
| Package 3 Width              | 30.000 cm |
| Package 3 Length             | 40.000 cm |
| Package 3 Weight             | 6.347 kg  |

## Logistical informations

|                   |    |
|-------------------|----|
| Country of origin | BE |
|-------------------|----|

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                                               |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                       | 2 kg CO2 eq.                                  |
| Carbon footprint of the manufacturing phase [A1 to A3] | 0.6 kg CO2 eq.                                |
| Carbon footprint of the distribution phase [A4]        | 0 kg CO2 eq.                                  |
| Carbon footprint of the installation phase [A5]        | 0 kg CO2 eq.                                  |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 1 kg CO2 eq.                                  |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 0.2 kg CO2 eq.                                |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

## Use Better



### Materials and Substances

|                                        |                                      |
|----------------------------------------|--------------------------------------|
| Packaging made with recycled cardboard | No                                   |
| Packaging without single use plastic   | Yes                                  |
| SCIP Number                            | 6763a476-30bc-4d05-a4bb-93f8d65c3771 |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again



### Repack and remanufacture

|                                 |                                                                                                                                                                                                                 |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recyclability potential, in %   | 62                                                                                                                                                                                                              |
| End of life manual availability | No need of specific recycling operations                                                                                                                                                                        |
| Take-back                       | No                                                                                                                                                                                                              |
| WEEE Label                      |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |