

SIMATIC IPC MD-34A Desk Dock accessories; MD-34A all configurations; 1x LAN 10/100 Mbps, 2x USB 2.0; 1x RS-232; 1x DP, DC-in 19 V side; 2x USB 2.0; use the MD-34A power supply cord for desk docking power cord of this desk docking is the same as MD-34A if you want to order an extra power cord

General information	
Design of the programming device	Mobile computer
Supply voltage	
Rated value (DC)	19 V
permissible range, lower limit (AC)	100 V
permissible range, upper limit (AC)	240 V
Interfaces	
Number of RS 232 interfaces	1
Number of USB interfaces	4
• Type A	4; 2* USB 2.0 in rear I/O 2* USB 2.0 in the side I/O
Video interfaces	
• DisplayPort	Yes
Industrial Ethernet	
• Industrial Ethernet interface	
— 100 Mbps	Yes; 1* 10/100 MBits/s
• Wake on LAN	No
• IAMT (Intel Active Management Technology)	No
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	-20 °C
• max.	60 °C
Ambient temperature during storage/transportation	
• min.	-30 °C
• max.	70 °C
Relative humidity	
• Operation, min.	50 %
• Operation, max.	95 %
Dimensions	
Width	292 mm
Height	133 mm
Depth	99 mm
Weights	
Weight, approx.	770 mg
Classifications	

	Version	Classification
eClass	14	27-33-02-92
eClass	12	27-33-02-92
eClass	9.1	27-33-02-92
eClass	9	27-33-02-92
eClass	8	27-24-92-03
eClass	7.1	27-24-92-03
eClass	6	27-24-92-03
ETIM	10	EC002584
ETIM	9	EC002584

ETIM	8	EC002584
ETIM	7	EC002584

Approvals / Certificates

General Product Approval	EMV	Maritime application
--------------------------	-----	----------------------

[Manufacturer Declaration](#)
[China RoHS](#)



Environment



last modified:

10/15/2025 