

Product datasheet

Specifications



braking resistor - 27 ohm - 100 W -
cable 3 m - IP65

VW3A7602R30

⚠ Discontinued on: 27 Aug 2020

⚠ End-of-service on: 24 Nov 2021

⚠ Discontinued

Main

Range of product	Altivar Lexium
Range compatibility	Lexium 15 Lexium 52 Lexium 28 Lexium 05 Lexium 32i
Product or component type	Braking resistor
Ohmic value	27 Ohm

Complementary

Energy peak	1900 J at 400 V 3800 J at 230 V 1900 J at 480 V 4200 J at 115 V
Continuous power	100 W
Protection type	Thermal protection via the servo drive
Net weight	0.9 kg
Cable length	3 m

Environment

IP degree of protection	IP65
Ambient air temperature for storage	-25...85 °C
Ambient air temperature for operation	0...50 °C

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)


Use Longer

Lifetime extension	
Repair	No

Dimensions Drawings

Braking Resistor

Dimensions



Dimensions in mm

b	b1	c	c1	H
145	110	15	15.5	98

Dimensions in in.

b	b1	c	c1	H
5.70	4.33	0.59	0.61	3.85