

Product data sheet

Specifications



DIO drop interface Modicon Quantum - 24 V DC - 2 redundant port

140CRA21220

⚠ To be discontinued on: 31 December 2022

⚠ To be end-of-service on: 31 December 2030

⚠ To be discontinued

Main

Range of product	Modicon Quantum automation platform
Product or component type	DIO drop interface

Complementary

Number of port	2 redundant
[Us] rated supply voltage	24 V DC
Supply voltage limits	20...30 V
Maximum supply current	1.6 A 24 V
Inrush current	30 A 24 V
Maximum buffer time	1 ms
Associated fuse rating	2.5 A
Output voltage	5.1 V
Nominal output current	3 A
Minimum load current	0 A
Short-circuit protection	With
Output overvoltage protection	With
I/O words	30 I/32 O
Typical backplanes	10 positions 2 positions 6 positions 3 positions 4 positions 16 positions
Diagnostics startup	RAM address Checksum RAM
Diagnostics run time	Checksum RAM RAM address
Power dissipation in W	11 W
Connections - terminals	Terminal block, 7 poles
Module format	Standard

Environment

Resistance to electrostatic discharge	4 kV contact conforming to IEC 801-2 8 kV on air conforming to IEC 801-2
Resistance to electromagnetic fields	10 V/m 80...2000 MHz conforming to IEC 801-3
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-40...85 °C
Relative humidity	95 % without condensation
Operating altitude	<= 5000 m
Protective treatment	TC
Standards	UL 508
Product certifications	UL C-Tick GOST CSA Class 1 Division 2 DNV

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.0 cm
Package 1 Width	16.0 cm
Package 1 Length	31.5 cm
Package 1 Weight	726.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	2
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	1.878 kg

Offer Sustainability


Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty

Warranty	18 months
----------	-----------


Racks for Modules Mounting

Dimensions of Modules and Racks



DC Powered Distributed I/O (DIO) Module

Wiring Diagram



Recommended replacement(s)

140CRA21220 is replaced by:

1x



Remote IO Drop E/IP, Modicon X80, standard

BMXCRA31200