

Product data sheet

Specifications



ASCO 5702 Power Management Gateway

ASCOCAM5702PMG

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Main

Product Type Monitoring unit

Complementary

Number of Devices	256
Voltage Rating	9...36 V DC
Power	45 W
Number of Ethernet Ports	4
Number of USB Ports	4
Number of Serial Ports	4
Number of Audio Ports	2
Device Mounting	Wall mounted
Solid State Drive Capacity	256 GB
Provided Equipment	Power supply
Height	7.6 in (192 mm)
Width	2.9 in (73 mm)
Depth	9.06 in (230 mm)
Product Weight	6.4 lb(US) (2.9 kg)

Environmental

Standards	UL IEC 60068-2-27
Operating Temperature	-4...122 °F (-20...50 °C)

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	7.6 in (19.2 cm)
Package 1 Width	2.9 in (7.3 cm)
Package 1 Length	9.06 in (23.0 cm)
Package weight(Lbs)	6.4 lb(US) (2.9 kg)

Contractual warranty

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

Use Longer



Lifetime extension

Repair

No