



CT Overload relay 180 - 250 A size S10 class 10 for motor protection for single mounting main circuit: screw terminal AUX. circuit: screw terminal manual automatic reset

product brand name	SIRIUS
product designation	Thermal overload relay
product type designation	3RU5
General technical data	
power loss [W] for rated value of the current at AC in hot operating state	
• per pole	0 W
type of calculation of power loss current-dependent	quadratic
surge voltage resistance rated value	8 kV
Substance Prohibitance (day/month/year)	09/03/2013
Net Weight	2.2 kg
Ambient conditions	
ambient temperature	
• during transport	-55 ... +80 °C
relative humidity during operation	0 ... 100 %
Main circuit	
number of poles for main current circuit	3
adjustable current response value current of the current-dependent overload release	1.8 ... 2.5 A
operating frequency rated value	50 ... 60 Hz
operational current rated value	2.5 A
Electrical Safety	
protection class IP on the front according to IEC 60529	IP20
touch protection on the front according to IEC 60529	finger-safe, for vertical contact from the front
Approvals Certificates	
General Product Approval	Maritime application other



[CCS \(China Classification Society\)](#)

[Confirmation](#)

other	Environment
-------	-------------



[Environmental Confirmations](#)

Further information

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/products?pnid=16027&lc=en-CN>

last modified:

4/3/2025 