

# Product datasheet

Specifications



## busbar EasyPact - 250 A - 6 ways

EZB250W06

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

### Main

Range of product	EasyPact
Range	EasyPact
Device short name	busbar
Product or component type	Busbar
Device application	Connection
Range compatibility	EasyPact EasyPact EZB circuit breaker
[In] rated current	250 A
Number of ways	6 ways

### Complementary

[Ui] rated insulation voltage	690 V AC 50/60 Hz
[Ue] rated operational voltage	550 V AC 50/60 Hz
Number of devices	18 (1P) 6 (3P) 8 (2P)
Busbar extension	Without
[Icw] rated short-time withstand current	30 kA for 1 s
Height	343.5 mm
Width	416 mm
Depth	82.5 mm

### Environment

Standards	IEC 60439
-----------	-----------

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

EU RoHS Directive

[Compliant](#)

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins