

# Product data sheet

Specifications



gearbox with straight teeth GBX- Ø  
80 mm- reduction 100:1- <  
16arcmin- 120 N.m

GBX0801001003F

⚠ Discontinued on: Sep 20, 2022

⚠ End-of-service on: Mar 31, 2025

⚠ Discontinued

## Main

|                           |                          |
|---------------------------|--------------------------|
| Range Compatibility       | Lexium 32                |
| Product or Component Type | Planetary gearbox        |
| Gear box type             | Straight teeth           |
| Device short name         | GBX                      |
| Gearbox external diameter | 3.1 in (80 mm)           |
| Product compatibility     | BSH1003...<br>BMH1003... |
| Reduction ratio           | 100:1                    |

## Complementary

|                            |  |
|----------------------------|--|
| Maximum torsional backlash | 16 arc.min   |
| Torsional rigidity         | 6.3 N.m/arcmin   |
| Housing Colour             | Black  |
| Housing material           | Black anodized aluminium   |
| Shaft material             | C 45   |
| Additional information     | Lubricated for life  |
| Service life in hours      | 30000 h 100 rpm 86 °F (30 °C)  |
| Efficiency                 | 94 %   |
| Maximum radial force Fr    | 650 N 100 rpm, force applied at mid-distance from output shaft during 30000 hour at 30 °C<br>950 N 100 rpm, force applied at mid-distance from output shaft during 10000 hour at 30 °C |
| Maximum axial force Fa     | 1200 N 100 rpm, during 10000 hour at 30°C<br>900 N 100 rpm, during 30000 hour at 30°C  |
| Continuous output torque   | 1062.09 lbf.in (120 N.m) 100 rpm 86 °F (30 °C)   |
| Maximum output torque      | 1699.3 lbf.in (192 N.m) 100 rpm 86 °F (30 °C)  |
| Net Weight                 | 6.8 lb(US) (3.1 kg)  |
| Compatibility code         | GBX  |

## Environment

|                                   |                            |
|-----------------------------------|----------------------------|
| Noise level                       | 60 dB 1 m, no-load         |
| IP Degree of Protection           | Shaft output IP54          |
| ambient temperature for operation | -13...194 °F (-25...90 °C) |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

# Packing Units

---

|                        |     |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

---

|                       |   |
|-----------------------|---|
| Nbr. of units in pkg. | 1 |
|-----------------------|---|

# Contractual warranty

---

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No