

SIMATIC Field PG M6 Advanced; i7-8850H (2.6 to 4.3 GHz; 6 kernels + hyper-threading; 9 MB Smart Cache); 15.6" display; Full HD (1920x 1080); WLAN 802.11ac & Bluetooth V5.0; DVD +/-RW; UHD Graphics 630; 2x 32 GB DDR4 SDRAM SO-DIMM; 2 TB SSD SATA (2.5"); with S5 interface, with S5-EPROMMER; incl. STEP 5 license; incl. S5-AG cable and EPROM adapter; Line cable with power plug: USA; Keyboard: QWERTZ/QWERTY; without NVME (M.2); Windows 10 IoT Enterprise (Version 1903), 64-bit; license for STEP 7 Professional Combo; WinCC Advanced Combo (TIA Portal & WinCC flexible); Safety Advanced Combo (TIA Portal & Distributed Safety); version of the pre-installed and licenses V16 including SINEMA RC Client 2.0

| General information | |
|--|--|
| Design of the programming device | Notebook |
| Display | |
| Design of display | 15.6" full HD display in 16:9 format |
| Resolution (pixels) | |
| <ul style="list-style-type: none"> Horizontal image resolution | 1 920 pixel |
| <ul style="list-style-type: none"> Vertical image resolution | 1 080 pixel |
| General features | |
| <ul style="list-style-type: none"> Non-reflecting | Yes |
| <ul style="list-style-type: none"> Luminance | 300 cd/m ² |
| Backlighting | |
| <ul style="list-style-type: none"> Type of backlighting | LED |
| Control elements | |
| Keyboard | |
| <ul style="list-style-type: none"> Design | QWERTZ/QWERTY or AZERTY (French); 87 keys |
| Touch operation | |
| <ul style="list-style-type: none"> Integrated touch pad | Yes; Clickpad |
| Supply voltage | |
| Design of the power supply | External wide-range power supply; 3-pole |
| permissible range, lower limit (AC) | 100 V; ±10 %, sinusoidal |
| permissible range, upper limit (AC) | 240 V; ±10 %, sinusoidal |
| Line frequency | |
| <ul style="list-style-type: none"> permissible range, lower limit | 47 Hz |
| <ul style="list-style-type: none"> permissible range, upper limit | 63 Hz |
| Processor | |
| Processor type | Intel Core i5-8400H (2.5 to 4.2 GHz, 4 cores and hyper-threading, 8 MB Smart Cache) or i7-8850H (2.6 to 4.3 GHz 6 cores and hyper-threading, 9 MB Smart Cache) |
| Chipset | Intel CM246 |
| Hyper-threading | Yes |
| Turbo Boost Technology 2.0 | Yes |
| Graphic | |
| Graphics controller | Intel® UHD Graphics 630 |
| Drives | |
| SSD | Yes; Easy to replace |
| <ul style="list-style-type: none"> Memory capacity | 256 Gbyte; Up to 2 TB SSD |
| TPM Security Chip | Yes; 2.0 (version for China without TPM) |
| Storage | |
| Type of memory | DDR4 SO-DIMM |
| Work memory | |
| <ul style="list-style-type: none"> Number of slots | 2; can be equipped with 1x 8 GB, 1x 16 GB, 1x 32 GB or 2x32 GB |
| Accumulator | |
| Replaceable | Yes; Lithium-ion battery |
| Capacity | 8.25 A·h |

| Interfaces | |
|---|--|
| Number of interfaces PROFIBUS DP | 1; 1x PROFIBUS DP / MPI; 9-pin Sub-D socket; 9.6 kBaud to 12 MBaud |
| Number of RS 232 interfaces | 1; 25-pin socket |
| Number of USB interfaces | 4 |
| • Type A | 3; 1x USB port incl. integrated charging function for USB devices (e.g. smartphone) - also with device switched off |
| • Type C | 1; USB 3.1 Gen. 2 |
| Number of chip-card readers | 1; Smart Card Reader (ISO/IEC 7816) |
| Bluetooth radio standard | Yes; V5.0 |
| Multimedia card/SD card slot | 2 in 1 (SDHC UHS-II, MMC) |
| Card reader for SIMATIC memory cards | SIMATIC memory cards (for S7-300/400), SMC (for S7-1x00), SIMATIC micro memory card (for S7-300/C7/ET 200) - including programming interfaces |
| Universal Audio Jack | Yes; Audio socket for 3.5 mm jack |
| Video interfaces | |
| • analog video signal (VGA) | Yes; via adapter from DVI to VGA |
| • DVI-I | Yes; 1x |
| • DisplayPort | Yes; 1x |
| Industrial Ethernet | |
| • Industrial Ethernet interface | 2x Ethernet (RJ45) |
| — 100 Mbps | Yes |
| — 1000 Mbps | Yes |
| • Wake on LAN | Yes |
| • IAMT (Intel Active Management Technology) | Yes |
| WLAN | |
| • Type | 802.11ac |
| Interrupts/diagnostics/status information | |
| LED status display | Battery status, device status, access to HDD/DVD, access to SD/MMC, MPI/DP, S5 and S7 modules / Card Reader (except Smart Card Reader), Num Lock, Caps Lock, WLAN active |
| EMC | |
| Interference immunity against discharge of static electricity | |
| • Interference immunity against discharge of static electricity acc. to IEC 61000-4-2 | Yes; ±4 kV contact discharge acc. to IEC 61000-4-2, ESD; ±8 kV air discharge acc. to IEC 61000-4-2, ESD |
| Interference immunity to cable-borne interference | |
| • Interference immunity on supply cables | ±2 kV (according to IEC 61000-4-4, burst); ±1 kV (according to IEC 61000-4-5, surge pulse/line to line); ±2 kV (according to IEC 61000-4-5, surge pulse/line to ground) |
| • Interference immunity on signal cables | ±1 kV (according to IEC 61000-4-4, burst, length < 30 m); ±2 kV (according to IEC 61000-4-4, burst, length > 30 m); ±2 kV (according to IEC 61000-4-5, surge sym./line to ground, length > 30 m) |
| Standards, approvals, certificates | |
| CE mark | Yes |
| CSA approval | Yes |
| UL approval | Yes |
| DIN/ISO 9001 | Yes |
| Ambient conditions | |
| Ambient temperature during operation | |
| • min. | 5 °C; Max. 10 °C/h (no condensation) |
| • max. | 40 °C; Max. 10 °C/h (no condensation) |
| Ambient temperature during storage/transportation | |
| • min. | -20 °C; Max. 20 °C/h (no condensation) |
| • max. | 60 °C; Max. 20 °C/h (no condensation) |
| Relative humidity | |
| • Operation, min. | 5 %; At 30 °C/h (no condensation); Tested according to IEC 60068-2-78, IEC 60068-2-30, IEC 60068-2-14 |
| • Operation, max. | 85 %; At 30 °C/h (no condensation); Tested according to IEC 60068-2-78, IEC 60068-2-30, IEC 60068-2-14 |
| Vibrations | |
| • Operation, tested according to IEC 60068-2-6 | Yes |
| Shock testing | |
| • tested according to IEC 60068-2-27 | Yes |
| Operating systems | |

| | |
|---|--|
| Local language of operating system | Multi-Language User Interface (MUI): 6 languages (English, German, French, Spanish, Italian, Chinese) |
| pre-installed operating system | |
| <ul style="list-style-type: none"> • Windows 10 • Windows 11 | Yes; Windows 10 IoT Enterprise 2021 LTSC Yes; Windows 11 IoT Enterprise (version 22H2) |
| Software | |
| Preinstalled | |
| <ul style="list-style-type: none"> • STEP 7 Professional (TIA Portal) • STEP 7 • WinCC flexible Advanced 2008 • WinCC Advanced (TIA Portal) • STEP 5 | Yes; software version: V16 Yes; Professional 2017 SR2 Yes; Software version: SP5 Yes; software version: V16 Yes; Optional; software version: STEP 5 V7.23 HF2 (incl. GRAPH 5/II V7.15) |
| Mechanics/material | |
| Material of housing | metal |
| Handle | Yes; retractable |
| Socket for Kensington lock | Yes |
| rubber corner guards | Yes |
| Dimensions | |
| Width | 385 mm |
| Height | 53 mm |
| Depth | 275 mm |
| Weights | |
| Weight, approx. | 3.4 kg; incl. rechargeable battery |
| Scope of supply | |
| Accumulator | Yes |
| Power supply | Yes |
| Backpack | Yes |
| SIMATIC Software | Yes |
| Recovery media | Yes; Restore & Recovery |
| Other | |
| free hotline | Yes |
| Note: | Made in Germany: development and production in Germany |

| Classifications | | | |
|------------------------|--------|----------------|-----------------------|
| | | Version | Classification |
| | eClass | 14 | 19-20-05-03 |
| | eClass | 12 | 19-20-05-03 |
| | eClass | 9.1 | 19-20-05-03 |
| | eClass | 9 | 19-20-05-03 |
| | eClass | 8 | 19-20-05-03 |
| | eClass | 7.1 | 27-24-22-10 |
| | eClass | 6 | 27-24-22-10 |
| | ETIM | 10 | EC001418 |
| | ETIM | 9 | EC001418 |
| | ETIM | 8 | EC001418 |
| | ETIM | 7 | EC001418 |

Approvals / Certificates

General Product Approval



[Miscellaneous](#)



[Confirmation](#)



| | | | |
|--------------------------|-----|-------------------|----------------------|
| General Product Approval | EMV | Test Certificates | Maritime application |
|--------------------------|-----|-------------------|----------------------|



[Miscellaneous](#)

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)



Maritime application

other



[Miscellaneous](#)



other

Environment

[Confirmation](#)

[Environmental Confirmations](#)



[Environmental Confirmations](#)

last modified:

11/25/2025