

# Product data sheet

Specifications



## TeSys LG - enclosed DOL starter - 0.16...0.25 A - 24 V AC coil

LG7K06B702

! Discontinued

### Main

|                                     |                                                                                                       |
|-------------------------------------|-------------------------------------------------------------------------------------------------------|
| Range                               | TeSys                                                                                                 |
| Product name                        | TeSys LG                                                                                              |
| Device short name                   | LG7K                                                                                                  |
| Product or component type           | Enclosed DOL starter                                                                                  |
| Device application                  | Safety                                                                                                |
| Utilisation category                | AC-3                                                                                                  |
| Device composition                  | Contactors<br>Circuit-breaker                                                                         |
| Motor power kW                      | 0.06 kW at 400/415 V AC 50/60 Hz<br>0.06 kW at 440 V AC 50/60 Hz                                      |
| Thermal protection adjustment range | 0.16...0.25 A                                                                                         |
| [Uc] control circuit voltage        | 24 V AC 50/60 Hz                                                                                      |
| Control type                        | Push-button start white I<br>Push-button stop black O<br>Mushroom head push-button emergency stop red |

### Complementary

|                    |                                                       |
|--------------------|-------------------------------------------------------|
| Standards          | IEC 60947-4-1<br>IEC 60204-1                          |
| Cable entry number | 4 2 Pg 13 + 2 Pg 16 top<br>4 2 Pg 13 + 2 Pg 16 bottom |
| Height             | 165 mm                                                |
| Depth              | 177 mm                                                |
| Product weight     | 1.3 kg                                                |
| Width              | 175 mm                                                |

### Environment

|                              |                              |
|------------------------------|------------------------------|
| Material                     | Polycarbonate                |
| IK degree of protection      | IK07 conforming to IEC 60529 |
| IP degree of protection      | IP55 conforming to IEC 60529 |
| Environmental characteristic | Standard environment         |

### Packing Units

|                        |     |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                              |         |
|------------------------------|---------|
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 17.5 cm |
| Package 1 Width              | 24.4 cm |
| Package 1 Length             | 17.5 cm |
| Package 1 Weight             | 1.6 kg  |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer

| Lifetime extension |    |
|--------------------|----|
| Repair             | No |

### Use Again

| Repack and remanufacture |                                                                                                                                                                                                               |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WEEE Label               |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |