

RCBO 32 A 2-pole 2-module C characteristic type AC 30 mA, permitted in all countries. Observe national installation regulations!

Model	
product brand name	SENTRON
product designation	RCBO
General technical data	
number of poles	2
number of poles with protection	1
design of pole	1P+N
tripping characteristic class	C
overvoltage category	3
degree of pollution	2
Voltage	
type of voltage of the operating voltage	AC
insulation voltage (U <sub>i</sub> ) rated value	264 V
surge voltage resistance rated value	4 V
tripping fault current rated value	30 mA
<ul style="list-style-type: none"> <li>operational current at AC rated value</li> </ul>	32 A
residual current type	AC
Supply voltage	
supply voltage	
<ul style="list-style-type: none"> <li>at AC rated value</li> </ul>	240V
operating frequency	50 Hz
supply voltage frequency rated value	50 Hz
Protection class	
protection class IP	IP20, if the distribution board is installed, with connected conductors
Breaking Capacity	
switching capacity current	
<ul style="list-style-type: none"> <li>according to EN 60898 rated value</li> </ul>	10 kA
<ul style="list-style-type: none"> <li>according to IEC 60947-2 rated value</li> </ul>	15 kA
short-circuit current breaking capacity (I <sub>cn</sub> ) according to EN 61009-1 rated value	10 kA
rated residual switching capacity (I $\Delta$ m) according to IEC 61009-1	10 kA
energy limitation class	3
Product details	
product feature touch protection	Yes
product component neutral conductor switching	Yes
Connections	
position of power supply cord	Either top or bottom
Mechanical Design	
height	90 mm
width	36 mm
depth	77 mm
installation depth	70 mm
number of modular width units	2
mounting position	any
Net Weight	99 999 kg
Environmental conditions	
influence of the surrounding temperature	Max. 95% humidity

<b>ambient temperature during operation</b>	
• minimum	-5 °C
• maximum	55 °C
<b>ambient temperature during storage</b>	
• minimum	-40 °C
• maximum	75 °C

### Approvals Certificates

<b>Environment</b>	<b>General Product Approval</b>
--------------------	---------------------------------

[Environmental Con-  
firmations](#)

[Environmental Con-  
firmations](#)

[Miscellaneous](#)



[Confirmation](#)



<b>General Product Ap- proval</b>	<b>other</b>	<b>Dangerous goods</b>
---------------------------------------	--------------	------------------------



EG-Konf.

[Miscellaneous](#)

[Confirmation](#)



[Miscellaneous](#)

[Transport Information](#)

### Further information

**Information on the packaging**

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

**Information for data generation and storage**

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SU1354-1RC32>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/5SU1354-1RC32>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SU1354-1RC32](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SU1354-1RC32)

**CAX-Online-Generator**

<https://www.siemens.com/cax>

**Tender specifications**

<https://www.siemens.com/specifications>

**Characteristic curves**

[https://curves.simarisiemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simarisiemens.com/curves/<mmp_prod_noCOMP=)

last modified:

7/22/2025

