


# Product datasheet

Specifications

## trip unit - TMD -125 - 4 poles 4d



30446

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

### Main

Range	ComPact
Range of product	NS100...250
Product or component type	Trip unit
Trip unit name	TM-DC
Trip unit technology	Thermal-magnetic
Range compatibility	ComPact NS100 DC ComPact NS160 DC ComPact NS250 DC
Device application	Distribution
Number of poles	4P
Protected poles description	3t
Protection type	for overload protection (thermal) for short-circuit protection (magnetic)
Trip unit rated current	125 A at 40 °C
Network type	DC

### Complementary

Long-time pick-up adjustment type $I_r$ (thermal protection)	Adjustable
[ $I_r$ ] long-time protection pick-up adjustment range	0.8...1 x $I_n$
Short-time protection pick-up adjustment type $I_{sd}$	Fixed
[ $I_{sd}$ ] Short-time protection pick-up adjustment range	1250 A

### Environment

Standards	IEC 60947-2
Product certifications	ASTA KEMA ASEFA LCIE
Pollution degree	3 conforming to IEC 60947
IP degree of protection	IP40 conforming to IEC 60529
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

# Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

# Contractual warranty

---

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins