

# Product datasheet

Specifications



## TeSys GC - modular contactor - 25 A - 4 NO - coil 12 V AC

GC2540J5

⚠ Discontinued on: 14 Jan 2021

EAN Code: 3389110571264

⚠ Discontinued

### Main

Range	TeSys
Product name	TeSys GC
Product or component type	Modular contactor
Device short name	GC25
Contactor application	Lighting Heating Motor control

### Complementary

Utilisation category	AC-7B AC-7A
Poles description	4P
power pole contact composition	4 NO
[Ue] rated operational voltage	$\leq 250$ V AC
[Ie] rated operational current	25 A AC-7A 8.5 A AC-7B
Operating position	30°/vertical
Control circuit type	AC at 50 Hz
[Uc] control circuit voltage	12 V AC 50 Hz
[Uimp] rated impulse withstand voltage	4 kV
[Ith] conventional free air thermal current	25 A (at 50 °C) for power circuit
Irms rated making capacity	68 A at 400 V AC for power circuit conforming to IEC 61095
Rated breaking capacity	68 A at 400 V for power circuit conforming to IEC 61095
[Icw] rated short-time withstand current	200 A 40 °C - 10 s for power circuit 62 A 40 °C - 30 s for power circuit
Associated fuse rating	25 A gL at $\leq 440$ V for power circuit
Average impedance	2.5 mOhm - Ith 25 A 50 Hz for power circuit
[Ui] rated insulation voltage	500 V conforming to IEC 61095 500 V conforming to VDE 0110
Electrical durability	AC-7A: 100000 cycles AC-7B: 100000 cycles
Power dissipation per pole	1.6 W
Control type	Remote control
Mounting mode	Clip-on

<b>Mounting support</b>	DIN rail
<b>Standards</b>	IEC 61095 IEC 60947-5
<b>Connections - terminals</b>	Control circuit: screw clamp terminals 1 cable(s) 2.5 mm <sup>2</sup> flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 2.5 mm <sup>2</sup> flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 2.5 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 1.5 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 1.5 mm <sup>2</sup> solid without cable end Control circuit: screw clamp terminals 2 cable(s) 1.5 mm <sup>2</sup> solid without cable end Power circuit: screw clamp terminals 1 cable(s) 6 mm <sup>2</sup> flexible without cable end Power circuit: screw clamp terminals 2 cable(s) 4 mm <sup>2</sup> flexible without cable end Power circuit: screw clamp terminals 1 cable(s) 6 mm <sup>2</sup> flexible with cable end Power circuit: screw clamp terminals 2 cable(s) 1.5 mm <sup>2</sup> flexible with cable end Power circuit: screw clamp terminals 1 cable(s) 6 mm <sup>2</sup> solid without cable end Power circuit: screw clamp terminals 2 cable(s) 4 mm <sup>2</sup> solid without cable end
<b>Tightening torque</b>	Control circuit: 0.8 N.m - on screw clamp terminals Power circuit: 0.8 N.m - on screw clamp terminals
<b>Operating time</b>	10...25 ms opening 10...30 ms closing
<b>Mechanical durability</b>	1000000 cycles
<b>Maximum operating rate</b>	300 cyc/h 50 °C
<b>Control circuit voltage limits</b>	Drop-out: 0.2...0.75 U <sub>c</sub> at 50 Hz (at <50 °C) Operational: 0.85...1.1 U <sub>c</sub> at 50 Hz (at <50 °C)
<b>Inrush power in VA</b>	34 VA 50 Hz (at 20 °C)
<b>Hold-in power consumption in VA</b>	4.6 VA 50 Hz (at 20 °C)
<b>Heat dissipation</b>	1.6 W at 50/60 Hz

## Environment

<b>IP degree of protection</b>	IP40 conforming to VDE 0106 (in enclosure) IP20 conforming to VDE 0106
<b>Protective treatment</b>	TC
<b>Ambient air temperature for operation</b>	-5...50 °C
<b>Ambient air temperature for storage</b>	-40...70 °C
<b>Operating altitude</b>	<= 3000 m
<b>Mechanical robustness</b>	Shocks contactor open: 10 Gn for 11 ms Shocks contactor closed: 15 Gn for 11 ms Vibrations contactor open: 2 Gn, 5...300 Hz Vibrations contactor closed: 3 Gn, 5...300 Hz
<b>Total number of 18 mm modules</b>	2
<b>Height</b>	85 mm
<b>Width</b>	36 mm
<b>Depth</b>	62.5 mm
<b>Net weight</b>	0.23 kg
<b>Quantity per set</b>	Set of 6
<b>Colour</b>	White

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	8 cm

---

Package 1 Width	9.5 cm
Package 1 Length	23 cm
Package 1 Weight	223 g

---

## Contractual warranty

---

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

SCIP Number

361e1245-bdfb-4c55-bca5-ee0430c46917

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins