

Product datasheet

Specifications



control block - for contactor ACTc - 230..240 V

18308

⚠ Discontinued on: 25 Feb 2019

⚠ Discontinued

Main

Product or component type	Double control input auxiliary
Device short name	ACTc
[Uc] control circuit voltage	230...240 V AC 50/60 Hz impulse 250 ms 230...240 V AC 50/60 Hz maintained

Complementary

Mounting mode	Fixed, on the left of CT
Mounting support	DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	60 mm
Connections - terminals	Tunnel type terminals 2 cable(s) 2.5 mm² flexible Tunnel type terminals 2 cable(s) 1.5 mm² rigid
Range compatibility	Multi9 Multi9 CT

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2 cm
Package 1 Width	7.9 cm
Package 1 Length	8.7 cm
Package 1 Weight	84 g

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins