

Product data sheet

Specifications

SQUARE D



Transformer, dry type, 15kVA, 3 phase, 600V delta primary, 208Y/120V secondary, 17D, 150C rise, Cu

EE15T65HCU

! Discontinued

! Discontinued on: Oct 11, 2022

Main

Product	Energy Efficient Transformer
Enclosure Code	17D
Enclosure Type	NEMA 2
Insulation Temperature	428 °F (220 °C)
Phase	3 phase
Primary Voltage	600 V delta
Power Rating	15 kVA
Secondary Voltage	208Y/120 V
Temperature Rise	150 °C
Winding Material	Copper

Ordering and shipping details

Category	16285-3 PH EE/TP1 15-75 KVA LVGP XFMR
Discount Schedule	PE2E
GTIN	785901559191
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	33.00 in (83.82 cm)
Package 1 Width	22.00 in (55.88 cm)
Package 1 Length	18.00 in (45.72 cm)
Package weight(Lbs)	979.175 lb(US) (444.146 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Circularity Profile	No need of specific recycling operations