

Product data sheet

Specifications



Connector module, Lexium 32i,
ethernet m12;4 inputs/2 outputs m8
sink,sto

VW3M9216

**Product availability: Non-Stock - Not normally stocked in
distribution facility**

Main

Range of Product	Lexium 32i
Product or Component Type	Connector module
Accessory / separate part category	Connection accessories
Electrical Connection	Industrial connector

Complementary

Product compatibility	Control unit LXM32i EtherCAT Control unit LXM32i Profinet
Accessory / separate part destination	Motor BMI with control unit Lexium 32i
Range Compatibility	Lexium 32i
Communication interface	EtherCAT Profinet
Input/output type	2 discrete outputs 4 discrete inputs
Discrete input logic	Sink
Safety Function	STO (safe torque off)
Net Weight	0.49 lb(US) (0.22 kg)

Ordering and shipping details

Category	US1PC5618289
Discount Schedule	PC56
GTIN	3606481274236
Returnability	No
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.3 in (8.4 cm)
Package 1 Width	4.6 in (11.6 cm)
Package 1 Length	6.6 in (16.8 cm)
Package weight(Lbs)	8.4 oz (237.0 g)

Contractual warranty

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer

Lifetime extension	
Repair	No


Use Again

Repack and remanufacture	
Take-back	No

Connections and Schema

Connections and Schema

Connection of I/O Module for CANopen with Industrial Connectors



Signal	Meaning
+24VDC	24 V signal power supply
0VDC	Reference potential to +24VDC
DI0	Digital input 0
DI1	Digital input 1
DI2	Digital input 2
DI3	Digital input 3
DQ0	Digital output 0
DQ1	Digital output 1
STO_A	Safety function STO
STO_COM	Reference potential for safety function STO
STO_B	Safety function STO
SHLD	Shield (grounded internally)
Tx+	Ethernet transmit signal +

Signal	Meaning
Tx-	Ethernet transmit signal -
Rx+	Ethernet receive signal +
Rx-	Ethernet receive signal -
NC	Not connected