

**UL 489****T&B Catalog Number:**

S201U-Z2

UPC Number:

66201917919

Status:

Active

Description:

1 pole, 2 amps rated at 240 VAC, UL 489 series miniature circuit breaker with thermal-magnetic trip device, Z trip curve, and 10kA interrupt current rating

Features

UL current limiting
Fast breaking time
Bus connection system
Wide range of accessories
Suitable for reverse feed

Application

For use as branch protection
Designed to provide maximum protection with a very low short circuit trip setting, such as semiconductor applications
For use with resistive loads

General

Mounting Method DIN Rail
Trip Type Thermal-magnetic
Number of Poles 1
Series S200U-Z
Terminal Type Screw

Approvals

UL Class UL 489

Dimension Information

H x W x D (inches) 3.62 x 0.69 x 2.79
H x W x D (mm) 92 x 17.5 x 71

Specifications

Rated Current (Amps) 2
Rated Voltage AC 240
Interrupt Rating (kA) 10
Trip Curve Z

Packaging

T&B Inner Pack 1
Package in Units 10
T&B Sold in UOM Each
T&B Weight Per UOM 0.32 lbs. Each

Application Support

Product Brochure Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321

