

# Product datasheet

Specifications



## TeSys Deca contactor - 3P(3 NO) - AC-3 - <= 440 V 32 A - 250 V DC coil

LC1D3265UD

⚠ Discontinued on: 10 Jun 2022

⚠ End-of-service on: 26 Nov 2024

⚠ Discontinued

### Main

|                                |                                                                                                                  |
|--------------------------------|------------------------------------------------------------------------------------------------------------------|
| Range                          | TeSys                                                                                                            |
| Range of product               | TeSys D                                                                                                          |
| Product or component type      | Contactor                                                                                                        |
| Device short name              | LC1D                                                                                                             |
| Contactor application          | Resistive load<br>Motor control                                                                                  |
| Utilisation category           | AC-1<br>AC-3                                                                                                     |
| Poles description              | 3P                                                                                                               |
| [Ue] rated operational voltage | Power circuit: <= 690 V AC 25...400 Hz<br>Power circuit: <= 300 V DC                                             |
| [Ie] rated operational current | 32 A (at <60 °C) at <= 440 V AC AC-3 for power circuit<br>50 A (at <60 °C) at <= 440 V AC AC-1 for power circuit |
| [Uc] control circuit voltage   | 250 V DC                                                                                                         |

### Complementary

|                                             |                                                                                                                                                                                                                                                                                                                           |
|---------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Motor power kW                              | 7.5 kW at 220...230 V AC 50/60 Hz<br>15 kW at 380...400 V AC 50/60 Hz<br>15 kW at 415...440 V AC 50/60 Hz<br>18.5 kW at 500 V AC 50/60 Hz<br>18.5 kW at 660...690 V AC 50/60 Hz                                                                                                                                           |
| Motor power hp                              | 2 hp at 115 V AC 50/60 Hz for 1 phase motors<br>5 hp at 230/240 V AC 50/60 Hz for 1 phase motors<br>7.5 hp at 200/208 V AC 50/60 Hz for 3 phases motors<br>10 hp at 230/240 V AC 50/60 Hz for 3 phases motors<br>20 hp at 460/480 V AC 50/60 Hz for 3 phases motors<br>30 hp at 575/600 V AC 50/60 Hz for 3 phases motors |
| Compatibility code                          | LC1D                                                                                                                                                                                                                                                                                                                      |
| Pole contact composition                    | 3 NO                                                                                                                                                                                                                                                                                                                      |
| Protective cover                            | Without                                                                                                                                                                                                                                                                                                                   |
| [Ith] conventional free air thermal current | 10 A (at 60 °C) for signalling circuit<br>50 A (at 60 °C) for power circuit                                                                                                                                                                                                                                               |
| Irms rated making capacity                  | 140 A AC for signalling circuit conforming to IEC 60947-5-1<br>250 A DC for signalling circuit conforming to IEC 60947-5-1<br>550 A at 440 V for power circuit conforming to IEC 60947                                                                                                                                    |
| Rated breaking capacity                     | 550 A at 440 V for power circuit conforming to IEC 60947                                                                                                                                                                                                                                                                  |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                                 |                                                                                                                                                                                                                                                                                                                                                            |
|-------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>[Icw] rated short-time withstand current</b> | 260 A 40 °C - 10 s for power circuit<br>430 A 40 °C - 1 s for power circuit<br>60 A 40 °C - 10 min for power circuit<br>138 A 40 °C - 1 min for power circuit<br>100 A - 1 s for signalling circuit<br>120 A - 500 ms for signalling circuit<br>140 A - 100 ms for signalling circuit                                                                      |
| <b>Associated fuse rating</b>                   | 10 A gG for signalling circuit conforming to IEC 60947-5-1<br>63 A gG at <= 690 V coordination type 1 for power circuit<br>63 A gG at <= 690 V coordination type 2 for power circuit                                                                                                                                                                       |
| <b>Average impedance</b>                        | 2 mOhm - lth 50 A 50 Hz for power circuit                                                                                                                                                                                                                                                                                                                  |
| <b>Power dissipation per pole</b>               | 2 W AC-3<br>5 W AC-1                                                                                                                                                                                                                                                                                                                                       |
| <b>[Ui] rated insulation voltage</b>            | Power circuit: 690 V conforming to IEC 60947-4-1<br>Power circuit: 600 V CSA certified<br>Power circuit: 600 V UL certified<br>Signalling circuit: 690 V conforming to IEC 60947-1<br>Signalling circuit: 600 V CSA certified<br>Signalling circuit: 600 V UL certified                                                                                    |
| <b>Overvoltage category</b>                     | III                                                                                                                                                                                                                                                                                                                                                        |
| <b>Pollution degree</b>                         | 3                                                                                                                                                                                                                                                                                                                                                          |
| <b>[Uimp] rated impulse withstand voltage</b>   | 6 kV conforming to IEC 60947                                                                                                                                                                                                                                                                                                                               |
| <b>Safety reliability level</b>                 | B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1                                                                                                                                                                                       |
| <b>Mechanical durability</b>                    | 30 Mcycles                                                                                                                                                                                                                                                                                                                                                 |
| <b>Electrical durability</b>                    | 1.65 Mcycles 32 A AC-3 at Ue <= 440 V<br>1.4 Mcycles 50 A AC-1 at Ue <= 440 V                                                                                                                                                                                                                                                                              |
| <b>Control circuit type</b>                     | DC standard                                                                                                                                                                                                                                                                                                                                                |
| <b>Coil technology</b>                          | Built-in bidirectional peak limiting diode suppressor                                                                                                                                                                                                                                                                                                      |
| <b>Control circuit voltage limits</b>           | 0.1...0.25 Uc (-40...70 °C):drop-out DC<br>0.7...1.25 Uc (-40...60 °C):operational DC<br>1...1.25 Uc (60...70 °C):operational DC                                                                                                                                                                                                                           |
| <b>Inrush power in W</b>                        | 5.4 W (at 20 °C)                                                                                                                                                                                                                                                                                                                                           |
| <b>Hold-in power consumption in W</b>           | 5.4 W at 20 °C                                                                                                                                                                                                                                                                                                                                             |
| <b>Operating time</b>                           | 53.55...72.45 ms closing<br>16...24 ms opening                                                                                                                                                                                                                                                                                                             |
| <b>Time constant</b>                            | 28 ms                                                                                                                                                                                                                                                                                                                                                      |
| <b>Maximum operating rate</b>                   | 3600 cyc/h 60 °C                                                                                                                                                                                                                                                                                                                                           |
| <b>Connections - terminals</b>                  | Control circuit: lugs-ring terminals - external diameter: 8 mm<br>Power circuit: lugs-ring terminals - external diameter: 10 mm                                                                                                                                                                                                                            |
| <b>Tightening torque</b>                        | Control circuit: 1.7 N.m - on lugs-ring terminals - with screwdriver flat Ø 6 mm M3.5<br>Control circuit: 1.7 N.m - on lugs-ring terminals - with screwdriver Philips No 2 M3.5<br>Power circuit: 2.5 N.m - on lugs-ring terminals - with screwdriver flat Ø 8 mm M4<br>Power circuit: 2.5 N.m - on lugs-ring terminals - with screwdriver Philips No 2 M4 |
| <b>Auxiliary contact composition</b>            | 1 NO + 1 NC                                                                                                                                                                                                                                                                                                                                                |
| <b>Auxiliary contacts type</b>                  | type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1<br>type mirror contact 1 NC conforming to IEC 60947-4-1                                                                                                                                                                                                                                   |
| <b>Signalling circuit frequency</b>             | 25...400 Hz                                                                                                                                                                                                                                                                                                                                                |
| <b>Minimum switching voltage</b>                | 17 V for signalling circuit                                                                                                                                                                                                                                                                                                                                |
| <b>Minimum switching current</b>                | 5 mA for signalling circuit                                                                                                                                                                                                                                                                                                                                |
| <b>Insulation resistance</b>                    | > 10 MOhm for signalling circuit                                                                                                                                                                                                                                                                                                                           |

|                  |                                                                                                         |
|------------------|---------------------------------------------------------------------------------------------------------|
| Non-overlap time | 1.5 ms on de-energisation between NC and NO contact<br>1.5 ms on energisation between NC and NO contact |
| Mounting support | Rail<br>Plate                                                                                           |

## Environment

|                                                       |                                                                                                                                                                                       |
|-------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standards                                             | CSA C22.2 No 14<br>EN 60947-4-1<br>EN 60947-5-1<br>IEC 60947-4-1<br>IEC 60947-5-1<br>UL 508                                                                                           |
| Product certifications                                | LROS (Lloyds register of shipping)<br>RINA<br>GOST<br>DNV<br>GL<br>BV<br>UL<br>CCC<br>CSA                                                                                             |
| IP degree of protection                               | IP20 front face conforming to IEC 60529                                                                                                                                               |
| Protective treatment                                  | TH conforming to IEC 60068-2-30                                                                                                                                                       |
| Climatic withstand                                    | conforming to IACS E10 exposure to damp heat<br>conforming to IEC 60947-1 Annex Q category D exposure to damp heat                                                                    |
| Permissible ambient air temperature around the device | -60...80 °C storage<br>-40...60 °C operation<br>60...70 °C with derating                                                                                                              |
| Operating altitude                                    | 0...3000 m                                                                                                                                                                            |
| Fire resistance                                       | 850 °C conforming to IEC 60695-2-1                                                                                                                                                    |
| Flame retardance                                      | V1 conforming to UL 94                                                                                                                                                                |
| Mechanical robustness                                 | Vibrations contactor open (2 Gn, 5...300 Hz)<br>Vibrations contactor closed (4 Gn, 5...300 Hz)<br>Shocks contactor closed (15 Gn for 11 ms)<br>Shocks contactor open (8 Gn for 11 ms) |
| Height                                                | 85 mm                                                                                                                                                                                 |
| Width                                                 | 45 mm                                                                                                                                                                                 |
| Depth                                                 | 99 mm                                                                                                                                                                                 |
| Net weight                                            | 0.535 kg                                                                                                                                                                              |

## Packing Units

|                              |     |
|------------------------------|-----|
| Unit Type of Package 1       | PCE |
| Number of Units in Package 1 | 1   |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer

| Lifetime extension |    |
|--------------------|----|
| Repair             | No |