

PRODUCT-DETAILS

ACS580-01-033A-4

LV AC general purpose wall-mounted drive, IEC:
Pn 15 kW, 32 A, 400 V, 480 V (ACS580-01-033A-4)



General Information

Global Commercial Alias	ACS580-01-033A-4
Product ID	3AXD50000038961
ABB Type Designation	ACS580-01-033A-4
EAN	6438177459262
Catalog Description	LV AC general purpose wall-mounted drive, IEC: Pn 15 kW, 32 A, 400 V, 480 V (ACS580-01-033A-4)

The ACS580-01 is plug-in ready to control your compressors, conveyors, pumps, extruders, centrifuges, mixers, fans and many other variable and constant torque applications, in a variety of light industries, including food and beverage, plastic, textile, material handling, and agriculture.

Long Description

All essential features are built-in as standard, simplifying drive selection, and making additional hardware unnecessary. Versatile and straightforward settings menu and assistants enable fast setup, commissioning, use and maintenance, while rugged and robust design makes it a good fit for various environments. With the ACS580 drives you can easily take full control of your processes to comprehensively manage your plant. The wall-mounted ACS580-01 comes in IP21 enclosure as standard. Also, IP55 and flange mounting units are available.

Ordering

Country of Origin	Romania (RO) Finland (FI) China (CN)
Customs Tariff Number	85044086
HS Code	850440-- Electrical transformers, static converters (for example, rectifiers) and

inductors.- Static converters

Invoice Description	ACS580-01-033A-4 PN: 15.0 kW, IN: 32 A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

Container Information

Gross Volume	22.779 dm ³
--------------	------------------------

Dimensions

Product Net Weight	11.8 kg 26.015 lb
Product Net Depth / Length	229.00 mm 9.02 in
Product Net Height	490.00 mm 19.29 in
Product Net Width	203.00 mm 7.99 in
Package Level 1 Depth / Length	295.00 mm 11.614 in
Package Level 1 Height	390.00 mm 15.354 in
Package Level 1 Width	600.00 mm 23.622 in
Package Level 1 Units	1 carton

Technical

Number of Phases	3
Degree of Protection	IP21
Enclosure Type NEMA	Type1
Altitude	1000 m 95
Sound dB (A)	76 dB(A)
Multiple Battery Information	Lithium Coin, CR2032, 220 mAh, 3 V, 1 pc, 3 g
Frequency (f)	47.5 ... 63 Hz
Frame Size	R3
Input Voltage (U _{in})	380 ... 480 V
Mounting Type	Wall-mounted
Communication Protocol	CAN DeviceNet EtherNet/IP MODBUS Other Bus Systems PROFIBUS PROFINET IO TCP/IP
Number of Hardware Interfaces	Industrial Ethernet 0 Other 2 Parallel 2 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1
Includes	Control unit PC connection

Analog Inputs	2
Analog Outputs	2
Number of Digital In/Outputs	6 / 3
Output Current, Heavy-Duty Use (I_{HD})	24.6 A
Output Current, Light-Overload Use (I_{LD})	30.4 A
Output Current, Normal Use (I_n)	32 A
Output Power, Heavy-Duty Use (P_{HD})	11.0 kW
Output Power, Light-Overload Use (P_{LD})	15.0 kW
Output Power, Normal Use (P_n)	15 kW
Apparent Power Output	22 kV·A
Efficiency Level	IE2
Standby Loss	16 W
Complete Drive Module Efficiency (61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	162 W	87.8 %	0.7 %
0/50 %	205 W	91.7 %	0.9 %
0/100 %	351 W	92.8 %	1.6 %
50/25 %	175 W	93.3 %	0.8 %
50/50 %	228 W	95.4 %	1.0 %
50/100 %	404 W	95.9 %	1.8 %
90/50 %	252 W	97.1 %	1.1 %
90/100 %	492 W	97.2 %	2.2 %

Temperature Rating	Maximum 40 °C Minimum -15 °C
--------------------	---------------------------------

Classifications

ETIM 8	EC001857 - Frequency converter =< 1 kV
ETIM 9	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

Environmental

SCIP	8e1cd225-4cd2-4db1-8a7b-419a51ce1ae3 Finland (FI)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Additional Information

Product Main Type	ACS580-01
Product Name	Frequency converter

Categories

Drives → Low Voltage AC Drives → General Purpose Drives → ACS580-01 - Wall-mounted drive

