

Product datasheet

Specifications



Isobar B - distribution board - 125 A - 400/415 V - 12 ways - IP55 - RAL 9001

MGBN12HDGR

⚠ Discontinued on: 15 Dec 2017

⚠ Discontinued

Main

| | |
|---------------------------|----------------------|
| Product or component type | Distribution board |
| enclosure type | Heavy-duty enclosure |
| Door type | Plain |

Complementary

| | |
|--------------------------------|-----------------------|
| Enclosure mounting | Surface |
| [Ie] rated operational current | 125 A at 400/415 V AC |
| Height | 850 mm |
| Width | 600 mm |
| Depth | 330 mm |

Environment

| | |
|-----------|---------------|
| Standards | BS EN 60439-3 |
|-----------|---------------|

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins