

Product datasheet

Specifications



TeSys Deca control relay, 5NO, 230V AC, bulk qty

CAD50P7TQ

Main

Range	TeSys TeSys Deca
Product name	TeSys CAD TeSys Deca
Product or component type	Auxiliary contactor
Device short name	CAD
Contact application	Control circuit
Utilisation category	AC-15 AC-14
Control circuit type	AC
Coil type	Standard
Suppressor technology	Without built-in
Pole contact composition	5 NO
[Uc] control circuit voltage	230 V AC 50/60 Hz
Connections - terminals	1 x 1...4 mm ² flexible with cable end 1 x 1...4 mm ² flexible without cable end 1 x 1...4 mm ² solid without cable end 2 x 1...2.5 mm ² flexible with cable end 2 x 1...4 mm ² flexible without cable end 2 x 1...4 mm ² solid without cable end
Quantity per set	Set of 10

Complementary

Contact operation	Mechanically linked conforming to IEC 60947-5-1
Control circuit voltage limits	Drop-out: 0.3...0.6 U _c Operational: 0.8...1.1 U _c at 50 Hz Operational: 0.85...1.1 U _c at 60 Hz
[Ui] rated insulation voltage	600 V - certifications CSA 600 V - certifications UL 690 V - overvoltage category III (pollution degree 3) - conforming to IEC 60947-5-1
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947
Tightening torque	1.7 N.m
[Ue] rated operational voltage	<= 690 V AC 25...400 Hz
[Ith] conventional free air thermal current	10 A (at 60 °C)
Irms rated making capacity	140 A at <= 690 V AC conforming to IEC 60947-5-1
Associated fuse rating	10 A gG at <= 690 V conforming to IEC 60947-5-1
Inrush power in VA	70 VA (at 20 °C)

Hold-in power consumption in VA	8 VA 50 Hz (at 20 °C)
Mechanical durability	30000000 cycles
Maximum operating rate	3 cyc/s 20 °C
Operating time	12...22 ms coil energisation and NO closing 4...12 ms coil de-energisation and NO opening 4...19 ms coil energisation and NC opening 6...16 ms coil de-energisation and NC closing
minimum switching current	5 mA
Minimum switching voltage	17 V
Non-overlap time	1.5 ms on de-energisation between NC and NO contacts 1.5 ms on energisation between NC and NO contacts
Insulation resistance	> 10 MOhm
Height	77 mm
Width	45 mm
Depth	86 mm
Net weight	0.58 kg

Environment

Standards	BS 4794 IEC 60947-5-1 NF C 63-140 EN 60947-5 VDE 0660 IEC 60335-1
Product certifications	CSA UL UKCA
IP degree of protection	IP2X conforming to VDE 0106
Protective treatment	TH conforming to IEC 60068
Ambient air temperature for operation	-40...70 °C at U _c -5...60 °C at 0.8...1.1 U _c
Ambient air temperature for storage	-60...80 °C
Operating altitude	3000 m without derating
Shock resistance	10 gn control relay open 15 gn control relay closed
Vibration resistance	2 gn 5...300 Hz control relay open 4 gn 5...300 Hz control relay closed

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	7.7 cm
Package 1 Length	8.6 cm
Package 1 Weight	12.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	24
Package 2 Height	15.0 cm

Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	743.0 g

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	17 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Carbon footprint of the manufacturing phase [A1 to A3]	3 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.3 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	11 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	B67ac941-f42f-4afd-894a-0b6f9cefde62
REACH Regulation	REACH Declaration

Use Longer




Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	66
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins