

# Product data sheet

Specifications



Masterpact breaker, MTZ3, cradle,  
4000-6000A rated, 3 pole, UL/ANSI  
listed

LV839336

## Main

Range	MasterPact
Product or component type	Cradle
type of accessory	Mounting accessory
Product compatibility	MasterPact MTZ3 40-60 H MasterPact MTZ3 40-60 L MasterPact MTZ3 40-60 HF MasterPact MTZ3 40-60 HB MasterPact MTZ3 40-60 HC MasterPact MTZ3 40-60 H2 MasterPact MTZ3 40-60 H3 MasterPact MTZ3 40-60 HA MasterPact MTZ3 40-60 L1
Poles description	3P

## Complementary

Mounting mode	Drawout
[Ie] rated operational current	4000...6000 A 104 °F (40 °C)

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

## Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

### Use Longer



#### Lifetime extension

Repair **No**

### Use Again



#### Repack and remanufacture

Take-back **No**