

Product data sheet

Specifications



ASCO 3164 Load Bank

ASCOLBLV3164

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Main

Product Type Resistive load bank

Complementary

Voltage Rating
380 V AC 50 Hz
400 V AC 50 Hz
415 V AC 50 Hz
480 V AC 60 Hz

Capacity Rating
1530 kW
1550 kW
1580 kW

Load Step Resolution 1 kW

Cooling System Rating 9509994.3 Gal/hr(US) (35998.6 m3/h)

Provided Equipment
1 gland plate
Cooling fans

Enclosure Material Zintec

Surface Finish Zinc plated

Color Gray

Connection Terminals Terminals inside)

Length 95.3 in (2420 mm)

Width 68.1 in (1730 mm)

Height 88.6 in (2250 mm)

Product Weight 4409.2 lb(US) (2000 kg)

Environment

Ambient Air Temperature 95 °F (35 °C)

Standards
ISO 9001
CE

IP Protection
IP1x
IP54

Contractual warranty

Warranty (in months) 18

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

Use Longer



Lifetime extension

Repair **No**