

Product datasheet

Specifications



Lexium 15 - Profibus DP fieldbus communication card - 9.6 kbps

VW3M3306

! Discontinued on: 27 Aug 2020

! End-of-service on: 18 Oct 2024

! Discontinued

Main

Product or component type	Communication card
Range compatibility	Lexium 15
Communication port protocol	Profibus DP fieldbus
Transmission rate	12 Mbps for bus length of 100 m 12 Mbps for bus length of 400 m with 3 repeaters 9.6 kbps for bus length of 1200 m 9.6 kbps for bus length of 4800 m with 3 repeaters

Complementary

Connector type	2 female SUB-D 9
Number of addresses	1...63
Installed device	32 Lexium 15 servo drives maximum without repeater
Communication service	Access to all the movement parameters and diagnostics parameters (4 PKW words) Control and status words External position, speed and torque setpoints PPO type 2 I/O data Access to the various motion task control words
Net weight	0.14 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No