

Product data sheet

Specifications



plug-in relay - Harmony RHK - latching - 4 C/O - 110 V AC 50 Hz - 5 A

RHK411F

⚠ Discontinued on: Aug 13, 2024

⚠ Discontinued

Main

Range of product	Harmony Relay
Product or component type	Plug-in relay
Device short name	RHK
Contacts type and composition	4 C/O
Contact operation	Latching Standard
[Uc] control circuit voltage	110 V AC 50 Hz
[Ithe] conventional enclosed thermal current	5 A 104 °F (40 °C)
status LED	Without
Control type	Manual control
Coil interference suppression	Without

Complementary

[Ui] rated insulation voltage	250 V
Test levels	Level A group mounting
Operating position	Any position
Minimum switching capacity	150 mVA 10 mA 150 mVA, 1 V
Contact bounce time	<= 10 ms
Maximum voltage drop	<100 V for 3 A at 24 V
Average resistance	30 mOhm 68 °F (20 °C)
Average coil consumption in VA	6 inrush) coil 1 1.3 holding) coil 2 2.5 inrush) coil 2 3.5 holding) coil 1
Control circuit voltage limits	0.8...1.1 Uc IEC 60255
Drop-out voltage threshold	0.15...0.5 Uc
Cos phi	0.6 inrush) 0.7 holding)
Mechanical durability	10000000 cycles
maximum operating rate	2 cyc/mn
Operating time	5...17 ms between energisation of coil and closing of NO contact 68 °F (20 °C) 8...16 ms between energisation of trip coil and closing of NC contact 68 °F (20 °C) 1...3 ms energisation/de-energisation 0.5...6 ms de-energisation/energisation

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Minimum pulse duration	50 ms
CAD overall width	1.3 in (33 mm)
CAD overall height	1.7 in (43 mm)
CAD overall depth	3.5 in (90 mm)
Terminals description ISO n°1	(21-22-24)OC (41-42-44)OC (31-32-34)OC (11-12-14)OC (B1-B2)CO (A1-A2)CO
Net weight	0.31 lb(US) (0.14 kg)
Compatibility code	RHK

Environment

Standards	VDE 0435 BS 4794 IEC 255 NF C 45-250
Product certifications	BV USSR CSA UR EDF ASE
Protective treatment	TC
Dielectric strength	2500 V
Ambient air temperature for operation	23...104 °F (-5...40 °C) IEC 60255
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Vibration resistance	6 gn (f= 10...55 Hz) conforming to IEC 60068-2-6 6 gn (f= 10...55 Hz) conforming to NF C 20-616
Shock resistance	30 gn 11 ms NF C 20-608

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.0 in (5 cm)
Package 1 Width	2.2 in (5.5 cm)
Package 1 Length	4.5 in (11.5 cm)
Package 1 Weight	5.4 oz (153 g)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained](#) >

[How we assess product sustainability](#) >

Use Better

Materials and Substances	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)

Use Longer

Lifetime extension	
Repair	No