

Product data sheet

Specifications

SQUARE D



Circuit breaker, Q4, 400A, 2 pole, 240VAC, 25kA, I-Line, thermal magnetic

Q422400AC

! Discontinued on: Jan 26, 2021

! Discontinued

Main

Product or component type	Circuit breaker
Trip Unit Technology	Thermal-magnetic

Complementary

[In] rated current	400 A
Number of Poles	2P
Breaking capacity code	Q4
Mounting Mode	I-Line
Magnetic Hold Current	2000 A
Magnetic Tripping Current	4000 A
Electrical connection	Lugs, load I-Line connection, line
Terminal identifier	AL400LA
Tightening torque	371.7 lbf.in (42 N.m) 0.08...0.5 in ² (50...300 mm ²) AWG 1...600 kcmil 371.7 lbf.in (42 N.m) 0.08...0.2 in ² (50...120 mm ²) AWG 1...250 kcmil
Height	11 in (279.4 mm)
Width	6 in (152.4 mm)
Depth	5.84 in (148.34 mm)

Environment

Certifications	IEC UL listed CSA
----------------	-------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained](#) >

[How we assess product sustainability](#) >



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

EU RoHS Directive

[Compliant](#)

Halogen content performance

Halogen free plastic parts product

PVC free

Yes

Use Longer



Lifetime extension

Repair

No