

7MF4633-1EY22-2AB6-Z Y01



Image similar

SITRANS P DS III, HART, 4-20 mA transmitter for level Measuring cell filling silicone oil normal cleaning Span 25 to 600 mbar (0.363 to 8.70 psi) Version for diaphragm pressure controller. Consider additional delivery time for Remote seal. Remote seals must be ordered with an additional article no. Process connection: 1/4-18 npt securing thread: 7/16-20 unf Die-cast aluminium housing, process flange bolts made of stainless steel International design english inscription documentation as cd None explosion protection Electric connection and cable inlet: cable gland m 20x1.5 Housing cover with window range, (LINEAR CHARACTERISTIC) Y01: ... to ... mbar, kpa, MPA

Notes

Successor/Substitute: 7MF03.-.....-.....
Please enter text for every Y option (using the Configurator).

List Price	Show prices
Customer Price	Show prices
Additional Services	For this product we can offer services like Spare Part Delivery/Repair/Exchange. You have currently no rights to enter the Service Web Shop for that. For further information & to order this service, please contact your local Spares&Repair Partner
	For this product we can offer extended warranty contracts EEO (material exchange for a single product) OEM RSC (Repair Service Contract for a whole machine) For further information & to order these services, please contact your local Siemens Service Partner
Service & Support (Manuals, Certificates, FAQs...)	Download

Product

Article Number (Market Facing Number)	7MF4633-1EY22-2AB6-Z Y01
Product Description	SITRANS P DS III, HART, 4-20 mA transmitter for level Measuring cell filling silicone oil normal cleaning Span 25 to 600 mbar (0.363 to 8.70 psi) Version for diaphragm pressure controller. Consider additional delivery time for Remote seal. Remote seals must be ordered with an additional article no. Process connection: 1/4-18 npt securing thread: 7/16-20 unf Die-cast aluminium housing, process flange bolts made of stainless steel International design english inscription documentation as cd None explosion protection Electric connection and cable inlet: cable gland m 20x1.5 Housing cover with window range, (LINEAR CHARACTERISTIC) Y01: ... to ... mbar, kpa, MPA
Product family	Not available
Product Lifecycle (PLM)	PM400:Phase Out Started
PLM Effective Date	Product phase-out since: 01/02/19
Notes	Successor/Substitute: 7MF03.-.....-..... Please enter text for every Y option (using the Configurator).

Price data

Price Group / Headquarter Price Group	8P1
List Price	Show prices
Customer Price	Show prices
Metal Factor	None

Delivery information

Export Control Regulations	ECCN : N / AL : N
Standard lead time ex-works	20 Day/Days
Net Weight (kg)	4.5 Kg
Product Dimensions (W x L x H)	Not available
Packaging Dimension	Not available
Package size unit of measure	Not available
Quantity Unit	1 Piece
Packaging Quantity	1

Additional Product Information

EAN	Not available
UPC	Not available
Commodity Code	90261029
LKZ_FDB/ CatalogID	FI01-1
Product Group	4770
Country of origin	France
Compliance with the substance restrictions according to RoHS directive	Since: 20/07/17
Product class	C: products manufactured / produced to order, which cannot be reused or re-utilised or be returned against credit.
WEEE (2012/19/EU) Take-Back Obligation	Yes

Classifications

Not available
