



Figure similar

Article No. : 1FK7042-2AK71-1BA1

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

| Engineering data      |             |
|-----------------------|-------------|
| Rated speed (100 K)   | 6,000 rpm   |
| Number of poles       | 8           |
| Rated torque (100 K)  | 1.5 Nm      |
| Rated current         | 2.5 A       |
| Static torque (60 K)  | 2.50 Nm     |
| Static torque (100 K) | 3.00 Nm     |
| Stall current (60 K)  | 3.55 A      |
| Stall current (100 K) | 4.40 A      |
| Moment of inertia     | 2.900 kgcm² |
| Efficiency            | 89.0 %      |

| Physical constants          |                               |
|-----------------------------|-------------------------------|
| Torque constant             | 0.68 Nm/A                     |
| Voltage constant at 20° C   | 44.5 V/1000*min <sup>-1</sup> |
| Winding resistance at 20° C | 1.15 Ω                        |
| Rotating field inductance   | 8.6 mH                        |
| Electrical time constant    | 7.50 ms                       |
| Mechanical time constant    | 2.15 ms                       |
| Thermal time constant       | 30 min                        |
| Shaft torsional stiffness   | 15,500 Nm/rad                 |
| Net weight of the motor     | 4.6 kg                        |

| Mechanical data          |                                                       |
|--------------------------|-------------------------------------------------------|
| Motor type               | Permanent-magnet synchronous motor                    |
| Motor type               | Compact                                               |
| Shaft height             | 48                                                    |
| Cooling                  | Natural cooling                                       |
| Radial runout tolerance  | 0.040 mm                                              |
| Concentricity tolerance  | 0.08 mm                                               |
| Axial runout tolerance   | 0.08 mm                                               |
| Vibration severity grade | Grade A                                               |
| Connector size           | 1                                                     |
| Degree of protection     | IP65                                                  |
| Design acc. to Code I    | IM B5 (IM V1, IM V3)                                  |
| Temperature monitoring   | Pt1000 temperature sensor                             |
| Electrical connectors    | Connectors for signals and power rotatable            |
| Color of the housing     | Standard (Anthracite RAL 7016)                        |
| Holding brake            | without holding brake                                 |
| Shaft end                | Feather key                                           |
| Encoder system           | Encoder AS24DQI: absolute encoder single-turn 24 bits |

| Optimum operating point |           |
|-------------------------|-----------|
| Optimum speed           | 5,000 rpm |
| Optimum power           | 1.0 kW    |

| Limiting data                     |           |
|-----------------------------------|-----------|
| Max. permissible speed (mech.)    | 9,000 rpm |
| Max. permissible speed (inverter) | 9,000 rpm |
| Maximum torque                    | 10.5 Nm   |
| Maximum current                   | 15.3 A    |

| Recommended Motor Module |          |
|--------------------------|----------|
| Rated inverter current   | 5 A      |
| Maximum inverter current | 15 A     |
| Maximum torque           | 10.30 Nm |