

# Product datasheet

Specifications



Circuit breaker frame, MasterPacT MTZ1 10L1, for MicroLogic Active, 1000A, 130kA/440VAC 50/60Hz (Icu), 3P, fixed

LV947132

## Main

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                          | MasterPacT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Product name                   | MasterPacT MTZ1 Active                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Product or component type      | Circuit breaker                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Device short name              | MTZ1 10 L1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Device application             | Power distribution protection                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Poles description              | 3P                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Control unit                   | Without control unit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Product compatibility          | control unit MicroLogic Active 1.0 E<br>control unit MicroLogic Active 1.0 EP<br>control unit MicroLogic Active 2.0 A<br>control unit MicroLogic Active 2.0 AP<br>control unit MicroLogic Active 2.0 E<br>control unit MicroLogic Active 2.0 EP<br>control unit MicroLogic Active 5.0 A<br>control unit MicroLogic Active 5.0 AP<br>control unit MicroLogic Active 5.0 E<br>control unit MicroLogic Active 5.0 EP<br>control unit MicroLogic Active 6.0 A<br>control unit MicroLogic Active 6.0 AP<br>control unit MicroLogic Active 6.0 E<br>control unit MicroLogic Active 6.0 EP |
| [In] rated current             | 1000 A at 40 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Performance type               | L1 130 kA 440 V AC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Suitability for isolation      | Yes conforming to EN/IEC 60947-2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Selectivity category           | Category A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Control type                   | Push-button                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Mounting mode                  | Fixed                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

## Complementary

|                                                      |                                                                                                                             |
|------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| [Icu] rated ultimate short-circuit breaking capacity | 150 kA at 220/415 V AC 50/60 Hz<br>130 kA at 440 V AC 50/60 Hz<br>100 kA at 525 V AC 50/60 Hz                               |
| [Ics] rated service short-circuit breaking capacity  | 150 kA at 220/415 V AC 50/60 Hz<br>130 kA at 440 V AC 50/60 Hz<br>100 kA at 525 V AC 50/60 Hz                               |
| [Icw] rated short-time withstand current             | 10 kA 0.5 s                                                                                                                 |
| [Icm] rated short-circuit making capacity            | 330 kA 220/415 V AC at 50/60 Hz<br>286 kA 440 V AC at 50/60 Hz<br>220 kA 525 V AC at 50/60 Hz<br>52 kA 690 V AC at 50/60 Hz |

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                                      |                                                                                                                          |
|------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Integrated instantaneous protection (DIN in kA peak) | 9...11 kA                                                                                                                |
| Sensor rating                                        | 400 A<br>630 A<br>800 A<br>1000 A                                                                                        |
| [Ui] rated insulation voltage                        | 1000 V AC 50/60 Hz                                                                                                       |
| [Uimp] rated impulse withstand voltage               | 12 kV                                                                                                                    |
| Power dissipation in W                               | 110 W                                                                                                                    |
| Power dissipation per pole                           | 36.7 W                                                                                                                   |
| Maximum breaking time                                | 9 ms                                                                                                                     |
| Maximum closing response time                        | 50 ms                                                                                                                    |
| Mounting support                                     | Base plate<br>Rails                                                                                                      |
| Upside connection                                    | Front<br>Rear                                                                                                            |
| Downside connection                                  | Front<br>Rear                                                                                                            |
| Connection pitch                                     | 70 mm                                                                                                                    |
| Mechanical durability                                | 12500 cycles with maintenance                                                                                            |
| Electrical durability                                | 3000 cycles 440 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>2000 cycles 690 V AC 50/60 Hz conforming to EN/IEC 60947-2 |
| Height (H)                                           | 301 mm                                                                                                                   |
| Width (W)                                            | 276 mm                                                                                                                   |
| Depth (D)                                            | 196 mm                                                                                                                   |
| Net weight                                           | 14 kg                                                                                                                    |
| Standards                                            | EN/IEC 60947-1<br>EN/IEC 60947-2                                                                                         |
| Product certifications                               | CE<br>CCC<br>EAC                                                                                                         |

## Environment

|                                       |                                                                                                                                          |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| IP degree of protection               | IP3X conforming to EN/IEC 60529                                                                                                          |
| IK degree of protection               | IK07 conforming to EN/IEC 62262                                                                                                          |
| Pollution degree                      | 3 conforming to IEC 60664-1                                                                                                              |
| Ambient air temperature for operation | -25...70 °C                                                                                                                              |
| Temperature derating table            | 40 °C ( 1000 A )<br>45 °C ( 1000 A )<br>50 °C ( 1000 A )<br>55 °C ( 1000 A )<br>60 °C ( 1000 A )<br>65 °C ( 1000 A )<br>70 °C ( 1000 A ) |
| Ambient air temperature for storage   | -40...85 °C                                                                                                                              |
| Operating altitude                    | 0...2000 m without derating<br>2000 m...5000 m with derating                                                                             |

## Packing Units

|                        |     |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

|                              |          |
|------------------------------|----------|
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 75 cm    |
| Package 1 Width              | 60 cm    |
| Package 1 Length             | 80 cm    |
| Package 1 Weight             | 32.87 kg |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                                               |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                       | 761 kg CO2 eq.                                |
| Carbon footprint of the manufacturing phase [A1 to A3] | 113 kg CO2 eq.                                |
| Carbon footprint of the distribution phase [A4]        | 3 kg CO2 eq.                                  |
| Carbon footprint of the installation phase [A5]        | 6 kg CO2 eq.                                  |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 601 kg CO2 eq.                                |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 37 kg CO2 eq.                                 |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

## Use Better



### Materials and Substances

|                                        |                                                                                        |
|----------------------------------------|----------------------------------------------------------------------------------------|
| Packaging made with recycled cardboard | Yes                                                                                    |
| Packaging without single use plastic   | No                                                                                     |
| SCIP Number                            | 16fac76b-9b6f-4616-9270-c1fea4a5e42c                                                   |
| EU RoHS Directive                      | <a href="#">Compliant By Exemption</a>                                                 |
| REACH Regulation                       | <a href="#">Reference contains Substances of Very High Concern above the threshold</a> |
| Halogen-free status                    | Product contains halogen above thresholds                                              |
| PVC free                               | No                                                                                     |
| Silicone-free                          | No                                                                                     |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again



### Repack and remanufacture

|                                 |                                                                                                                                                                                                                 |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recyclability potential, in %   | 90                                                                                                                                                                                                              |
| End of life manual availability | <a href="#">End of Life Information</a>                                                                                                                                                                         |
| Take-back                       | No                                                                                                                                                                                                              |
| WEEE Label                      |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |



Technical Illustration

Dimensions

