

initialization module for automatic parameterization of SIMOCODE M series, for fixed mounting in switchboard



General technical data	
product brand name	SIMOCODE
product designation	Initialization module
ambient temperature	
<ul style="list-style-type: none"> <li>during storage</li> <li>during operation</li> <li>during transport</li> </ul>	-40 ... +80 °C -25 ... +70 °C -40 ... +80 °C
relative humidity during operation	5 ... 95 %

Certificates/ approvals			
General Product Approval	EMV	other	Environment



[Confirmation](#)



Environment	Industrial Communication
-------------	--------------------------

[Environmental Con-  
firmations](#)



Profibus

Further information
---------------------

### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UF8902-0AA00-0>

### Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UF8902-0AA00-0>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3UF8902-0AA00-0>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3UF8902-0AA00-0&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UF8902-0AA00-0&lang=en)

