



Lexium 32C, 32A, 32M and 32S servo drives (continued)						
Output current at 8 kHz		Nominal power at 8 kHz	Line current (2)	Max. prospective line Isc	Reference	Weight
Continuous (rms)	Peak (rms)(1)					
A	A	kW	A	kA		kg/lb
Three-phase supply voltage: 208 V ~ 50/60 Hz, with integrated EMC filter (3)						
1.8	6	0.35	1.8	5	LXM32CU60N4	1.700/ 3.748
					LXM32AU60N4	
					LXM32MU60N4	1.800/ 3.968
					LXM32SU60N4	
3.6	12	0.7	3.6	5	LXM32CD12N4	1.800/ 3.968
					LXM32AD12N4	
					LXM32MD12N4	1.900/ 4.189
					LXM32SD12N4	
6.2	18	1.2	6.2	5	LXM32CD18N4	2.000/ 4.409
					LXM32AD18N4	
					LXM32MD18N4	2.100/ 4.630
					LXM32SD18N4	
9.8	30	2	9.8	5	LXM32CD30N4	2.600/ 5.732
					LXM32AD30N4	
					LXM32MD30N4	2.700/ 5.952
					LXM32SD30N4	
21.9	72	5	21.9	5	LXM32CD72N4	4.800/ 10.582
					LXM32AD72N4	
					LXM32MD72N4	
					LXM32SD72N4	
Three-phase supply voltage: 480 V ~ 50/60 Hz, with integrated EMC filter (3)						
1.5	6	0.4	1.2	5	LXM32CU60N4	1.700/ 3.748
					LXM32AU60N4	
					LXM32MU60N4	1.800/ 3.968
					LXM32SU60N4	
3	12	0.9	2.4	5	LXM32CD12N4	1.800/ 3.968
					LXM32AD12N4	
					LXM32MD12N4	1.900/ 4.189
					LXM32SD12N4	
6	18	1.8	4.5	5	LXM32CD18N4	2.000/ 4.409
					LXM32AD18N4	
					LXM32MD18N4	2.100/ 4.630
					LXM32SD18N4	
10	30	3	7	5	LXM32CD30N4	2.600/ 5.732
					LXM32AD30N4	
					LXM32MD30N4	2.700/ 5.952
					LXM32SD30N4	
24	72	7	14.6	5	LXM32CD72N4	4.800/ 10.582
					LXM32AD72N4	
					LXM32MD72N4	
					LXM32SD72N4	
32	85	9	19.9	5	LXM32MD85N4	9.600/ 21.164
40	100	11	23.3	5	LXM32MC10N4	

(1) Maximum value for 5 seconds

(2) Without line choke (see page 27)

(3) Additional EMC filters available as an option (see page 28)

