



Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device Application	Heavy application
Disconnect Type	Fusible disconnect
Factory Installed Neutral	None
Phase	3 phase
Number of Poles	4
Current Rating	60 A
Voltage Rating	600 V AC/DC
Enclosure Rating	NEMA 1 steel
Motor power hp	15 Hp at 480 V AC 50-60 Hz for 2 phases motors 40 Hp at 480 V AC 50-60 Hz for 2 phases motors 20 Hp at 600 V AC 50-60 Hz for 2 phases motors 50 Hp at 600 V AC 50-60 Hz for 2 phases motors 10 Hp at 250 V DC 30 hp at 600 V DC

Complementary

Short Circuit Current Rating	10 KA H or K 200 kA R or J
Fuse type	H or K R or J
Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	4-wire
Wire Size	AWG 14...AWG 3 copper AWG 12...AWG 3 aluminium
Tightening torque	50 Lbf.In (5.65 N.m) (AWG 3) 45 Lbf.In (5.08 N.m) (AWG 6...AWG 4) 40 Lbf.In (4.52 N.m) 0.01 in ² (8.367 mm ²) (AWG 8) 50 lbf.in (5.65 N.m) 0.00...0.01 in ² (2.06...5.261 mm ²) (AWG 14...AWG 10)
Depth	6.85 in (173.99 mm)
Width	16.13 in (409.70 mm)
Height	20.5 in (520.70 mm)
Net Weight	28.66 lb(US) (13 kg)

Environment

Certifications	UL listed file E2875
----------------	----------------------

Ordering and shipping details

Category	00008-H&HU SW,2&3P,N1,30-200A
Discount Schedule	DE1
GTIN	785901482475
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.10 in (18.034 cm)
Package 1 Width	16.80 in (42.672 cm)
Package 1 Length	25.70 in (65.278 cm)
Package 1 Weight	17.48 lb(US) (7.929 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------