



SIMATIC HMI connection box decentralized for Mobile Panels, wall mounting, PROFINET and PROFIsafe, connection of safety relay, emergency stop circuit jumper, terminal detection, Integrated switch, MRP client, IRT, panel present

General information	
Product type designation	Connection box
Product function	
Web-based management	Yes
FH technology	
Safety evaluation through direct wiring	
Reconnection without emergency stop circuit interruption	Yes
Reconnection with emergency stop circuit interruption	No
Monitoring the STOP button	Yes
Monitoring of emergency stop button	Yes
Monitoring of acknowledgement button	Yes
Safety evaluation via PROFIsafe	
Reconnection without emergency stop circuit interruption	Yes
Reconnection with emergency stop circuit interruption	No
Monitoring the STOP button	Yes
Monitoring of emergency stop button	Yes
Monitoring of acknowledgement button	Yes
Installation type/mounting	
Wall mounting/direct mounting	Yes
Control cabinet installation	No
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	95 mA
Starting current inrush I ² t	0.16 A ² ·s
Power	
Active power input, typ.	2.3 W
Interfaces	
Number of industrial Ethernet interfaces	3
Number of PROFINET interfaces	3
Connection point identification	Yes
Industrial Ethernet	
Industrial Ethernet status LED	3
Protocols	
PROFINET	Yes
IRT	Yes

PROFIsafe	Yes
EtherNet/IP	Yes
AS-Interface	No
EIB/KNX	No
Protocols (Ethernet)	
• TCP/IP	Yes
• DHCP	Yes
• SNMP	Yes
• DCP	Yes
• LLDP	Yes
Redundancy mode	
Media redundancy	
— MRP	Yes
Further protocols	
• MODBUS	Yes
• other bus systems	No
EMC	
Emission of radio interference acc. to EN 55 011	
• Limit class A, for use in industrial areas	No
• Limit class B, for use in residential areas	No
Degree and class of protection	
IP degree of protection	IP65
IP65 (all-round)	Yes
IP (at the front)	IP65
Standards, approvals, certificates	
CE mark	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
KC approval	No
Suitable for safety functions	Yes
Highest safety class achievable in safety mode	
• Performance level according to ISO 13849-1	PLe
• SIL acc. to IEC 61508	SIL 3
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C
Relative humidity	
• Operation, max.	90 %
Configuration	
Configuration software	
• STEP 7 Professional (TIA Portal)	No
• WinCC Comfort (TIA Portal)	Yes; Optional
• WinCC Advanced (TIA Portal)	Yes; Optional
• WinCC Professional (TIA Portal)	Yes; Optional
Mechanics/material	
Enclosure material (front)	
• Plastic	Yes
• Aluminum	No
• Stainless steel	No
Dimensions	
Width of the housing front	230 mm
Height of housing front	145 mm
Depth of housing	76 mm
Weights	
Weight (without packaging)	0.72 kg
Weight (with packaging)	0.8 kg
Classifications	

	Version	Classification
eClass	14	27-33-02-92
eClass	12	27-33-02-92
eClass	9.1	27-33-02-92
eClass	9	27-33-02-92
eClass	8	27-24-92-03
eClass	7.1	27-24-92-03
eClass	6	27-24-92-03
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584

Approvals / Certificates

General Product Approval	EMV
--------------------------	-----

[Manufacturer Declaration](#)


EG-Konf.



[China RoHS](#)


RCM


RCM

Functional Safety	other
-------------------	-------

[TUEV](#)

[Type Examination Certificate](#)

[Type Examination Certificate](#)

last modified:

2/16/2025 