

# Product datasheet

Specifications



Auxiliary contact, Acti9, OFsp, 1 NC  
+ 1 C/O, 230VAC, 110VDC,  
0.1...6A, for RCCB-ID 125A

A9N16940

## Main

range of product	Acti9
Product or component type	OC contact
Device short name	OFSP
Signal contacts composition	1 NC + 1 C/O
[In] rated current	AC-15 0.1...6 A at 230 V, AC 50 Hz 0.1...1 A at 110 V, DC
9 mm pitches	1
Standards	IEC/EN 60947-5-1
Product certifications	CE

## Complementary

Range compatibility	Acti9 RCCB-ID 125A
Mounting mode	Fixed
Mounting location	Left side
Mounting support	DIN rail
Comb busbar and distribution block compatibility	NO
Height	86 mm
Width	9 mm
Depth	76 mm
Net weight	40 g
Colour	Grey
Connections - terminals	Tunnel type terminal1 cable(s) 1...1.5 mm <sup>2</sup> - flexible Tunnel type terminal1 cable(s) 1...1.5 mm <sup>2</sup> - rigid
Wire stripping length	8 mm
Tightening torque	0.8 N.m

## Environment

IP degree of protection	IP20 conforming to IEC/EN 60947-5-1
Pollution degree	3 conforming to IEC/EN 60947-5-1
Ambient air temperature for operation	-25...40 °C
Ambient air temperature for storage	-40...85 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	2.700 cm
<b>Package 1 Width</b>	8.100 cm
<b>Package 1 Length</b>	9.500 cm
<b>Package 1 Weight</b>	49.000 g
<b>Unit Type of Package 2</b>	S02
<b>Number of Units in Package 2</b>	45
<b>Package 2 Height</b>	15.000 cm
<b>Package 2 Width</b>	30.000 cm
<b>Package 2 Length</b>	40.000 cm
<b>Package 2 Weight</b>	2.520 kg

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	0.5 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.5 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0 kg CO2 eq.

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	429095ee-388a-4184-bea4-16f87e374975
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>

## Use Longer




### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	29
End of life manual availability	<a href="#">No need of specific recycling operations</a>
Take-back	Nej
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins