



RCBO, 10 kA, 1P+N, type A, 10 mA, B char., In: 6 A, Un AC: 230 V

Figure similar

| Model  |   |
|--|---|
| product brand name   | SENTRON   |
| product designation  | RCBO  |
| design of the product  | Instantaneous   |
| General technical data   |   |
| number of poles  | 2   |
| number of poles with protection  | 1   |
| design of pole   | 1P+N  |
| tripping characteristic class  | B   |
| mechanical service life (operating cycles) typical   | 10 000  |
| overvoltage category   | 3   |
| degree of pollution  | 2   |
| Voltage  |   |
| type of voltage of the operating voltage   | AC  |
| insulation voltage (Ui) rated value  | 264 V   |
| surge voltage resistance rated value   | 4 000 V   |
| surge current resistance at (8/20) $\mu$ s   | 1 kA  |
| tripping fault current rated value   | 10 mA   |
| <ul style="list-style-type: none"> <li>• operational current                             <ul style="list-style-type: none"> <li>— at 30 °C rated value</li> <li>— at 40 °C rated value</li> <li>— at 45 °C rated value</li> <li>— at 50 °C rated value</li> <li>— at 55 °C rated value</li> <li>— at 60 °C rated value</li> <li>— at 65 °C rated value</li> <li>— at 70 °C rated value</li> </ul> </li> <li>• operational current at AC rated value</li> </ul> | <ul style="list-style-type: none"> <li>6 A</li> <li>5.7 A</li> <li>5.58 A</li> <li>5.4 A</li> <li>5.22 A</li> <li>5.1 A</li> <li>4.86 A</li> <li>4.62 A</li> <li>6 A</li> </ul> |
| residual current type  | A   |
| Supply voltage   |   |
| supply voltage <ul style="list-style-type: none"> <li>• at AC rated value</li> <li>• for testing equipment minimum</li> </ul>  | <ul style="list-style-type: none"> <li>230/240 V</li> <li>100 V</li> </ul>  |
| operating frequency  | 50 Hz   |
| supply voltage frequency rated value   | 50 Hz   |
| Protection class   |   |
| protection class IP  | IP20, if the distribution board is installed, with connected conductors   |

| Breaking Capacity   |       |
|---|-------|
| <b>switching capacity current</b>   |       |
| • according to EN 60898 rated value   | 10 kA |
| • according to IEC 60947-2 rated value  | 35 kA |
| <b>short-circuit current breaking capacity (I<sub>cn</sub>) according to EN 61009-1 rated value</b> | 10 kA |
| <b>rated residual switching capacity (I<sub>Δm</sub>) according to IEC 61009-1</b>                  | 10 kA |
| <b>energy limitation class</b>  | 3     |

| Dissipation           |       |
|-----------------------|-------|
| <b>power loss [W]</b> |       |
| • maximum             | 2.8 W |

| Product details                               |     |
|---|-----|
| <b>product feature touch protection</b>       | Yes |
| product component neutral conductor switching | Yes |
| <b>product feature halogen-free</b>           | Yes |
| <b>product feature silicon-free</b>           | Yes |

| Connections   |                      |
|---|----------------------|
| <b>connectable conductor cross-section solid</b>                                    |                      |
| • minimum   | 0.75 mm <sup>2</sup> |
| • maximum   | 35 mm <sup>2</sup>   |
| <b>connectable conductor cross-section stranded</b>                                 |                      |
| • minimum   | 0.75 mm <sup>2</sup> |
| • maximum   | 35 mm <sup>2</sup>   |
| <b>connectable conductor cross-section finely stranded with core end processing</b> |                      |
| • minimum   | 0.75 mm <sup>2</sup> |
| • maximum   | 25 mm <sup>2</sup>   |
| <b>tightening torque with screw-type terminals</b>                                  |                      |
| • minimum   | 2.5 N·m              |
| • maximum   | 3 N·m                |
| <b>position of power supply cord</b>  | Either top or bottom |

| Mechanical Design                    |       |
|--------------------------------------|-------|
| <b>height</b>                        | 90 mm |
| <b>width</b>                         | 36 mm |
| <b>depth</b>                         | 77 mm |
| <b>installation depth</b>            | 70 mm |
| <b>number of modular width units</b> | 2     |
| <b>mounting position</b>             | any   |
| <b>Net Weight</b>                    | 277 g |

| Environmental conditions   |                   |
|--|-------------------|
| <b>influence of the surrounding temperature</b>                                    | Max. 95% humidity |
| <b>ambient temperature during operation</b>  |                   |
| • minimum  | -25 °C            |
| • maximum  | 55 °C             |
| <b>ambient temperature during storage</b>  |                   |
| • minimum  | -40 °C            |
| • maximum  | 75 °C             |
| <b>number of test cycles for environmental testing according to IEC 60068-2-30</b> | 28                |

| Approvals Certificates |                                 |
|------------------------|---------------------------------|
| <b>Environment</b>     | <b>General Product Approval</b> |

[Environmental Con-  
firmations](#)

[Environmental Con-  
firmations](#)



[Miscellaneous](#)

General Product Approval

EMV

Test Certificates



[Confirmation](#)



[Miscellaneous](#)

Test Certificates Maritime application other

[Special Test Certificate](#)



[Miscellaneous](#)



[Confirmation](#)

[Miscellaneous](#)

Railway Dangerous goods

[Special Test Certificate](#)

[Confirmation](#)

[Transport Information](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SU1154-6KK06>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SU1154-6KK06>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SU1154-6KK06](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SU1154-6KK06)

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)



last modified:

7/22/2025 

