

Product datasheet

Specifications



bar-mounted contactor - TeSys LC1-BM - 1 pole - AC-1 440V 1250 A - coil 440V AC

LC1BM31R22

⚠ Discontinued on: 1 Aug 2024

⚠ Discontinued

Main

Range	TeSys
Product name	TeSys B
Product or component type	Contacteur
Device short name	LC1BM
Contacteur application	Motor-heating-lighting
Utilisation category	AC-1
Control circuit type	AC
Coil type	Standard
Poles description	1P
Pole contact composition	1 NO
[Ie] rated operational current	1250 A (at <40 °C) AC AC-1 for power circuit
Auxiliary contact composition	2 NO + 2 NC
[Uc] control circuit voltage	440 V AC 50...400 Hz

Complementary

Control circuit voltage limits	Drop-out: 0.3...0.5 U _c at 50...400 Hz Operational: 0.85...1.1 U _c at 50...400 Hz
[U _i] rated insulation voltage	1000 V - for power circuit conforming to IEC 60158-1 1000 V - for power circuit conforming to IEC 60947-4 1500 V - for power circuit conforming to VDE 0110 group C
Mounting mode	Fixed
Mounting support	Bar support bracket Notched mounting rails
Tightening torque	Power circuit: 35 N.m - on bars
[U _e] rated operational voltage	Power circuit: ≤ 1000 V AC 50/60 Hz
[I _{th}] conventional free air thermal current	1250 A (at 40 °C) for power circuit
Irms rated making capacity	10000 A at 1000 V AC for power circuit conforming to IEC 60158-1 10000 A at 1000 V AC for power circuit conforming to IEC 60947-4
Rated breaking capacity	10000 A at 440 V for power circuit conforming to IEC 60158-1 10000 A at 440 V for power circuit conforming to IEC 60947-4 4000 A at 1000 V for power circuit conforming to IEC 60158-1 4000 A at 1000 V for power circuit conforming to IEC 60947-4 8000 A at 660...690 V for power circuit conforming to IEC 60158-1 8000 A at 660...690 V for power circuit conforming to IEC 60947-4 9000 A at 500 V for power circuit conforming to IEC 60158-1 9000 A at 500 V for power circuit conforming to IEC 60947-4

Associated fuse rating	1200 A aM at ≤ 440 V for power circuit 1200 A gI at ≤ 440 V for power circuit 1500 A gI at ≤ 440 V for power circuit
Average impedance	0.18 mOhm - Ith 1250 A 50 Hz for power circuit
Power dissipation per pole	280 W AC-1 - Ith 1250 A
Inrush power in VA	620 VA
Hold-in power consumption in VA	10 VA 50/60 Hz
Operating time	100...150 ms closing 50...100 ms opening
Mechanical durability	1200000 cycles
Maximum operating rate	120 cyc/h 55 °C
Height	490 mm
Width	375 mm
Depth	475 mm
Net weight	31 kg

Environment

Standards	IEC 60158-1 VDE 0660 BS 5424 NF C 63-110 IEC 60947-4
Product certifications	CSA RINA BV
Protective treatment	TC TH
Ambient air temperature for operation	-5...55 °C
Ambient air temperature for storage	-60...80 °C
Operating altitude	3000 m without derating



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No