

# Product datasheet

Specifications



universal protection relay,  
PowerLogic P3U20, 4L ringlug, 1U,  
10DI/5DO, Uaux: 48-230V, DI:  
220-230V, 2 x RJ-45

REL52045

## Main

|                                |                                                                                                |
|--------------------------------|------------------------------------------------------------------------------------------------|
| Range of product               | PowerLogic P3                                                                                  |
| Product or component type      | Protection relay                                                                               |
| Relay application              | Universal                                                                                      |
| product reference              | P3U20-6AAA3ACAA                                                                                |
| Mounting case size             | 20TE                                                                                           |
| power supply                   | 48...230 V AC/DC                                                                               |
| measuring inputs               | : 1/5 A CT phase current 3<br>: 1/5 A CT residual current 1<br>: 100 V/110 V VT voltage 1      |
| Number of sensors              | 0 temperature sensor(s)<br>0 arc sensor(s)                                                     |
| number of Digital Inputs (DI)  | 10                                                                                             |
| number of analogue inputs      | 0                                                                                              |
| number of Digital Outputs (DO) | 1 watchdog<br>5                                                                                |
| number of analogue outputs     | 0                                                                                              |
| communication ports            | USB port 1 front<br>RJ45 2 rear                                                                |
| communication protocols        | IEC 61850 ed. 1<br>IEC 61850 ed. 2<br>IEC 60870-5-101<br>DNP3 TCP<br>Modbus TCP<br>EtherNet/IP |
| Cybersecurity                  | Password protection<br>Port hardening                                                          |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| protection functions            | Phase undercurrent 37<br>Negative sequence overcurrent 46<br>Broken conductor 46 I2/I1<br>Excessive starting time, locked rotor 48/51LR<br>Thermal overload protection 49<br>Phase overcurrent 50/51<br>Earth fault overcurrent 50N/51N<br>Breaker failure 50BF<br>Switch ON to fault (SOTF)<br>Capacitor bank unbalance 51C<br>Capacitor overvoltage 59C<br>Neutral voltage displacement 59N<br>Motor restart inhibition 66<br>Directional earth fault 67N<br>Transient earth fault 67NI<br>CT supervision 60<br>VT supervision 60<br>H2 detection 68H2<br>H5 detection 68H5<br>Recloser 79<br>Lockout relay 86<br>Cold load pick-up<br>Programmable stages 99<br>Programmable curve                                                                                                                                                                         |
| Arc flash protection            | No                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| measurement functions           | Current 3-phase<br>Current zero sequence<br>Current positive sequence<br>Current negative sequence<br>Current ratio of negative and positive<br>Voltage phase to earth<br>Voltage phase to phase<br>Voltage zero sequence<br>Voltage positive sequence<br>Voltage negative sequence<br>Voltage ratio of negative and positive<br>Short circuit fault reactance<br>Fault location current<br>Earth fault reactance<br>Frequency<br>Active power<br>RMS active power<br>Reactive power<br>RMS reactive power<br>Apparent power<br>RMS apparent power<br>Active energy<br>Reactive energy<br>Cos $\varphi$<br>Tan $\varphi$<br>Power angle<br>Power factor<br>Voltage phasor diagram view<br>Current phasor diagram view<br>Current 2nd, 15th harmonics with THD<br>Voltage 2nd, 15th harmonics with THD<br>Voltage interruption<br>Condition monitoring CB wear |
| control functions               | Switchgear control and monitoring<br>Programmable switchgear interlocking<br>Local control on single-line diagram<br>Local control with I/O keys<br>Local/remote control<br>2 function keys<br>Mobile application with Easergy SmartApp<br>Web-server<br>Programmable logic                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| controllable switchgear devices | 2 controlled + 4 displayed                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| number of setting groups        | 4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| monitoring functions            | Trip circuit supervision 74<br>Circuit breaker monitoring<br>Relay self-monitoring                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

|                           |                                                                                                                            |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------|
| logs and records          | Event recording<br>Disturbance recording<br>Tripping context                                                               |
| Switchgear diagnosis type | CT supervision<br>Trip circuit supervision ANSI code: TCS                                                                  |
| Connections - terminals   | Screw removable (digital input/output)<br>Ring lugs removable (current transformer)<br>Pin removable (voltage transformer) |

## Complementary

|                     |                                                |
|---------------------|------------------------------------------------|
| Operating threshold | 220...230 V AC/DC                              |
| Software name       | EcoStruxure Power Device<br>ESetup Easergy Pro |
| Web server          | Embedded HTTP server                           |
| Display type        | LCD 128 x 64 pixels with single line diagram   |
| Number of key       | 2 customizable                                 |
| Local signalling    | 4 LEDs<br>8 LEDs programmable                  |
| Standards           | IEC                                            |
| Height              | 169.5 mm                                       |
| Width               | 170 mm                                         |
| Depth               | 205 mm                                         |
| Net weight          | 2.5 kg maximum                                 |

## Environment

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| climatic withstand                    | Exposure to dry heat Bb tests conforming to EN/IEC 60068-2-2<br>Exposure to cold Ad tests conforming to EN/IEC 60068-2-1<br>Exposure to damp heat in service Db tests conforming to EN/IEC 60068-2-30<br>Exposure to damp heat in service Cab tests conforming to EN/IEC 60068-2-78                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Mechanical robustness                 | Vibrations (level: class II) conforming to IEC 60255-21-1<br>Vibrations: Fc conforming to IEC 60068-2-6<br>Shocks (level: class II) conforming to IEC 60255-21-2<br>Shocks: Ea conforming to IEC 60068-2-27<br>Seismic tests method A (level: class II) conforming to IEC 60255-21-3<br>Bumps (level: class II) conforming to IEC 60255-21-2<br>Bumps: Ea conforming to IEC 60068-2-27                                                                                                                                                                                                                                                                                                                                                                                            |
| Electromagnetic compatibility         | Emission tests conforming to IEC/EN 60255-26 ed. 3<br>Emission tests conforming to CISPR 11<br>Emission tests conforming to CISPR 22<br>EMC immunity conforming to IEC/EN 60255-26 ed. 3<br>EMC immunity conforming to EN/IEC 61000-4-18<br>EMC immunity level 4 conforming to EN/IEC 61000-4-2<br>EMC immunity level 3 conforming to EN/IEC 61000-4-3<br>EMC immunity level 4 conforming to EN/IEC 61000-4-4<br>EMC immunity level 3 conforming to EN/IEC 61000-4-5<br>EMC immunity level 3 conforming to EN/IEC 61000-4-6<br>EMC immunity conforming to EN/IEC 61000-4-8<br>EMC immunity level 5 conforming to EN/IEC 61000-4-9<br>EMC immunity conforming to EN/IEC 61000-4-29<br>EMC immunity conforming to EN/IEC 61000-4-11<br>EMC immunity conforming to EN/IEC 61000-4-17 |
| Ambient air temperature for operation | -40...65 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Ambient air temperature for storage   | -40...70 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| IP degree of protection               | IP54 conforming to IEC 60529                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| maximum operating altitude            | 2000 m                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Protective treatment                  | Conformal coating                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

|                   |                                |
|-------------------|--------------------------------|
| Relative humidity | 0...95 %, without condensation |
|-------------------|--------------------------------|

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 21 cm    |
| Package 1 Width              | 26 cm    |
| Package 1 Length             | 31.5 cm  |
| Package 1 Weight             | 2.562 kg |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 24 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                                               |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                       | 696 kg CO2 eq.                                |
| Carbon footprint of the manufacturing phase [A1 to A3] | 64 kg CO2 eq.                                 |
| Carbon footprint of the distribution phase [A4]        | 3 kg CO2 eq.                                  |
| Carbon footprint of the installation phase [A5]        | 0.1 kg CO2 eq.                                |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 624 kg CO2 eq.                                |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 5 kg CO2 eq.                                  |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

## Use Better



### Materials and Substances

|                                        |                                                                                        |
|----------------------------------------|----------------------------------------------------------------------------------------|
| Packaging made with recycled cardboard | Yes                                                                                    |
| Packaging without single use plastic   | No                                                                                     |
| SCIP Number                            | 7fd15df9-a702-4a28-ad01-afb36a7b785f                                                   |
| EU RoHS Directive                      | <a href="#">Compliant By Exemption</a>                                                 |
| REACH Regulation                       | <a href="#">Reference contains Substances of Very High Concern above the threshold</a> |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again




### Repack and remanufacture

|                                 |                                                                                                                                                                                                                 |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recyclability potential, in %   | 32                                                                                                                                                                                                              |
| End of life manual availability | <a href="#">End of Life Information</a>                                                                                                                                                                         |
| Take-back                       | No                                                                                                                                                                                                              |
| WEEE Label                      |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

## Connections and Schema


## Functional View



Dimensions Drawings

Base Unit Dimensions

mm  
in.



|                         | A            | B           |
|-------------------------|--------------|-------------|
| With screw connector    | 214 mm/8.43" | 192 mm/7.6" |
| With ring-lug connector | 226 mm/8.90" | 204 mm/8.0" |