

Product datasheet

Specifications



Uniflair Chilled Water Unit, EC fans, Upflow, 20-170 kW

LUCV

Overview

Presentation	For the specifications, please refer to the product brochure and catalogue
Lead time	Special Order - Call for Quoted Lead Times

Main

Main Input Voltage	400 V 3 phases
--------------------	----------------

General

Air discharge option	Upflow
----------------------	--------

Physical

Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Network frequency	50 Hz
-------------------	-------

Conformance

Product certifications	CE
------------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins