

Product datasheet

Specifications



CANALIS COM BOX FOR FEEDER 250A

KSA250ABCB4

EAN Code: 3606480527821

Main

Range of product	Canalis
Product name	KS
Device short name	KSA
Product compatibility	Canalis KSA busbar trunking 100...250 A
Offer type	Advanced
Product or component type	Communication box
Conductors material	Aluminium
[Ue] rated operational voltage	230...690 V
Number of circuits	1
Protection type	Without protection
Control type	Communicating
Colour	White (RAL 9001)

Complementary

Provided equipment	End cover
Mounting location	Feed units
Mounting support	Busbar
Body material	Metal
Width	411.5 mm
Depth	127 mm
Height	310 mm
Net weight	4.8 kg
Standards	IEC 61439-1 IEC 61439-6

Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	23.000 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Width	41.000 cm
Package 1 Length	43.500 cm
Package 1 Weight	5.200 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	6
Package 2 Height	85.000 cm
Package 2 Width	62.000 cm
Package 2 Length	92.000 cm
Package 2 Weight	61.000 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Free of Substances of Very High Concern above the threshold
Halogen-free status	Halogen free product
PVC free	Yes
Silicone-free	Yes

Use Longer

 Lifetime extension	
Repair	No

Use Again

 Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Dimensions Drawings

Dimensions

