



Representative Image

## Catalog No. 2TLA020070R6600

**Description:** PLUTO D45 SAFETY-PLC

**UPC No** 7320500410646

**Home > Machine Safety > Programmable Safety Controllers**

Pluto is a cost effective, powerful and compact safety PLC for all machine safety applications. Most safety devices on the market can be connected directly to Pluto and multiple safety sensors can be connected to a single input and still achieve the highest safety level. Programming is done easily in the accompanying software Pluto Manager. Safety PLC with Pluto safety bus and analogue inputs. Totally 45 I/O: 8 combined failsafe analogue and digital inputs + 16 failsafe inputs + 15 non-failsafe outputs/failsafe inputs + 4 individually failsafe relay outputs + 2 individually failsafe transistor outputs. Analogue input range 0-10V/4-20mA.

### Descriptors

Category	Programmable Safety Controllers
----------	---------------------------------

### Specifications

Supply Voltage	24VDC
Product Main Type	Pluto
With Safety Bus	Yes
Safe Outputs	4NO Failsafe (Relay) + 2 Failsafe (Transistor)
Safe inputs/non-failsafe outputs/safe analog inputs	8 combined failsafe analogue and digital inputs + 16 failsafe inputs + 15 non-failsafe outputs/failsafe inputs
Product Class	Safety Programmable Logic Controllers
Degree of Protection	IP20(Terminals) and IP40(Enclosure)

### Classifications

ETIM 4	EC001449 - Device for monitoring of safety-related circuits
ETIM 5.0	EC001449 - Device for monitoring of safety-related circuits
ETIM 6.0	EC000236 - PLC CPU-module
ETIM 7	EC000236 - PLC CPU-module
ETIM 8 (Etim8)	EC000236 - PLC CPU-module

### Dimensions

Product Net Depth / Length	120 mm
Product Net Height	84 mm
Product Net Width	90 mm
Product Net Weight	0.65kg

### Safety Information

Performance Level	Up to e
-------------------	---------

