

Product datasheet

Specifications



Easergy P3 accessory VIO12AASE 24-230V RTD module 12 RTD inputs Optical Tx

REL52811

Main

Range of product	Easergy P3
Product or component type	Analog temperature module
Mounting support	35 mm symmetrical DIN rail Wall mounted
[Us] rated supply voltage	24...230 V AC/DC

Complementary

Communication port support	Fiber optic Serial link
Number of inputs	12 RTD (temperature sensor)
Temperature probe type	Pt 100, Ni 100, Ni 120, Cu 10

Environment

Ambient air temperature for operation	0...55 °C
---------------------------------------	-----------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.7 cm
Package 1 Width	9.8 cm
Package 1 Length	26.2 cm
Package 1 Weight	1.1 kg
Unit Type of Package 2	S03
Number of Units in Package 2	4
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	5.46 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No

Connections and Schema

Functional View

